Lawrence Livermore National Laboratory

Flux Concentrator and Vacuum Seal Test Update



Tom Piggott, Jeff Gronberg, Jay Javedani, Ryan Abbott, Ed Cook, Craig Brooksby, Charles Brown

Lawrence Livermore National Laboratory, P. O. Box 808, Livermore, CA 94551 This work performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under Contract DE-AC52-07NA27344

Desired flux concentrator pulse shape



Energizing device with 5 coils



Lawrence Livermore National Laboratory



Flux concentrating disks enhance the field



Lawrence Livermore National Laboratory



Coil currents vary with field location



Lawrence Livermore National Laboratory

Initial analysis using simplified coil



Compute inductance and induced field



Lawrence Livermore National Laboratory

Coil design choices and tradeoffs

- Number of turns per coil
- Parallel or series connections between coil
 - I_act=I_desired/N_turns
 - More turns, more voltage drop, more insulation
 - V=L(dI/dt)
 - L scales with N^2
 - dl/dt scales with 1/N
 - V scales with N
- Design of pulse-forming network depends on inductances and resistances of coils and connectors



Analyzing real coil geometry



Lawrence Livermore National Laboratory



Current and field in multiple turn coil



Lawrence Livermore National Laboratory

Initial PFN design

- Coils connected in series
- 25 kA current

– i(vsen)

kΑ

 4 turns in coil 1, 2 in coil 2, 1 in coils 3-5

- Designing PFN to power device
- Using SPICE to evaluate current output and rise time from PFN design

Including connector effects

30.0 25.0 20.0 current 15.0 10.0 5.0 0.0 -5.0 -0.0 0.5 1.0 1.5 2.0 2.5 3.0 3.5 4.0 time ms

Lawrence Livermore National Laboratory

Insulator evaluation

- Kapton recommendation of magnet manufacturer (Wang NMR)
- Collaborating with DESY to evaluate radiation suitability of insulator material
- Kapton manufacturer radiation damage threshold is 100 MGy



Flux concentrator layout



Lawrence Livermore National Laboratory

Current support bolt layout





Non-conductive support bolts

Lawrence Livermore National Laboratory



Stress calculation in disks

Stress input as a pressure on the bore interior



Lawrence Livermore National Laboratory

Structural Behavior

- Evaluating stress relief for fatigue life
- Bolt sizes and arrangement
- Additional strain relief from confinement/ case possible solution



Tensile Stress





Temperatures



Lawrence Livermore National Laboratory



Fluid velocity and pressure



Flow Velocity

Pressure

Lawrence Livermore National Laboratory

Continuing flux concentrator analysis

- Final design phase tasks
 - Structural support changes
 - Evaluation of coil voltages, tradeoffs relating this with connector and power supply hardware
 - Connector evaluation and selection
 - Insulator radiation survival analysis
- Preparation for prototyping
 - Developing detailed assembly drawings
 - Test plan, particularly evaluating possibilities for testing without full cooling plant
 - Obtain LLNL ES & H approved safety plan

Flux concentrator test plan

- Initial tests at low pulse rate, room temperature (uncooled)
 - Characterize magnetic field
 - Validate predictions of decay time constant for field
- Tests at low pulse rate, cryogenic temperature
 - See pulse flat-top over pulse duration
- Full system test (5 Hz operation, cryogenic temperature)

Rotating vacuum seal test

- Evaluating commercial ferrofluidic seals
 - Leakage (vacuum/fluid)
 - Magnetic field effects
 - Vibration



22

Vacuum seal test

- Using existing tank (\$100K) at LLNL
 - large enough to hold Daresbury prototype target wheel and flux concentrator for future tests
 - Initial test with equivalent weight only





Vacuum seal layout

- Altered layout after discussions with Rigaku
- Single-shaft design, larger bore
- Hollow shaft motor Rigaku has used previously
 - Alternative connections (non-belt drive) being considered
- Water union may not be in this test configuration





Vacuum seal test

- Rotordynamics analysis and design for cantilevered layout
 - Changed layout from Daresbury test
 - Requires re-evaluation of vibration modes due to new components and configuration
- Diagnostics setup (pressure sensors, filter and witness plate chemical analysis, mechanical behavior)
- Developing drawings
- Acquire LLNL ES & H approval for operating plan

