




Main Linac (Un)Reliability

Nick Walker

131st ILC@DESY meeting

01.04.2016


Main Linac Tunnel Cross-Section



Based on “SLAC”
“worst conceivable
accident” criteria

18MW continuous
power deposition
into a single “point”

Main Linac Tunnel Cross-Section



Best Safety
Solution:

Don't let them in!


Shielding still needed to
protect equipment in
service tunnel side and
allow RF commissioning
without beam.

(dark current and x-rays)

Why let them in in the first place?

Availability arguments


“AVIALSIM”
simulations



RDR/TDR: “two tunnels” cheaper than additional required linac overhead
Klystron+modulator lifetimes now expected to be much higher (100k vs 40k hours)

Why let them in in the first place?


Availability arguments



RDR/TDR: “two tunnels” cheaper than additional required linac overhead
Klystron+modulator lifetimes now expected to be much higher (100k vs 40k hours)

Why let them in in the first place?


Availability arguments



RDR/TDR: “two tunnels” cheaper than additional required linac overhead
Klystron+modulator lifetimes now expected to be much higher (100k vs 40k hours)



AVAILSIM model





AVAILSIM model

- Monte Carlo simulation

AVAILSIM model

- Monte Carlo simulation
- Models failure of
 - ▶ RF power chain
 - klystrons, modulators, LLRF electronics...
 - ▶ Cryomodule
 - cavity (?), tuner motor, coupler, coupler motor...
 - quadrupole, power supply etc.

AVAILSIM model

- Monte Carlo simulation
 - Models failure of
 - ▶ RF power chain
 - klystrons, modulators, LLRF electronics...
 - ▶ Cryomodule
 - cavity (?), tuner motor, coupler, coupler motor...
 - quadrupole, power supply etc.
 - **Maintenance philosophy**
 - ▶ Impact of single failure ("Failure Modes & Effect Analysis")
 - ▶ How many can be tolerated (overhead)
 - ▶ How things get fixed during scheduled maintenance
-


AVAILSIM model

- Monte Carlo simulation
 - Models failure of
 - ▶ RF power chain
 - klystrons, modulators, LLRF electronics...
 - ▶ Cryomodule
 - cavity (?), tuner motor, coupler, coupler motor...
 - quadrupole, power supply etc.
 - **Maintenance philosophy**
 - ▶ Impact of single failure ("Failure Modes & Effect Analysis")
 - ▶ How many can be tolerated (overhead)
 - ▶ How things get fixed during scheduled maintenance
 - **Time required to recover luminosity from unscheduled down**
 - ▶ Leads to cascaded events along machine
-


GIGO

- **Input:**

- ▶ Mean time to failure (MTTF)
- ▶ Lifetime Distribution Function
 - Exponential, Weibull, "bathtub", etc.



GIGO




- **Input:**

- ▶ Mean time to failure (MTTF)
- ▶ Lifetime Distribution Function
 - Exponential, Weibull, "bathtub", etc.

MTTF (hours)	TDR	TODAY
Klystron	40,000	100,000
Modulator	100,000	500,000
Power supply	100,000	500,000
Electronics	100,000	500,000

GIGO

- **Input:**
 - ▶ Mean time to failure (MTTF)
 - ▶ Lifetime Distribution Function
 - Exponential, Weibull, etc.




MTTF (hours)	TDR	TODAY
Klystron	40,000	100,000
Modulator	100,000	500,000
Power supply	100,000	500,000
Electronics	100,000	500,000

10MW MBK vendor estimates

GIGO

- **Input:**
 - ▶ Mean time to failure (MTTF)
 - ▶ Lifetime Distribution Function
 - Exponential, Weibull, etc.




MTTF (hours)	TDR	TODAY
Klystron	40,000	100,000
Modulator	100,000	500,000
Power supply	100,000	500,000
Electronics	100,000	500,000

10MW MBK vendor estimates
Solid-state with built-in redundancy

GIGO

- **Input:**

- ▶ Mean time to failure (MTTF)
- ▶ Lifetime Distribution Function
 - Exponential, Weibull, etc.




MTTF (hours)	TDR	TODAY
Klystron	40,000	100,000
Modulator	100,000	500,000
Power supply	100,000	500,000
Electronics	100,000	500,000

10MW MBK vendor estimates
Solid-state with built-in redundancy
Solid-state with built-in redundancy

GIGO

- **Input:**
 - ▶ Mean time to failure (MTTF)
 - ▶ Lifetime Distribution Function
 - Exponential, Weibull, etc.




MTTF (hours)	TDR	TODAY
Klystron	40,000	100,000
Modulator	100,000	500,000
Power supply	100,000	500,000
Electronics	100,000	500,000

10MW MBK vendor estimates
Solid-state with built-in redundancy
Solid-state with built-in redundancy
???

GIGO

- **Input:**
 - ▶ Mean time to failure (MTTF)
 - ▶ Lifetime Distribution Function
 - Exponential, Weibull, etc.



*All theoretical
No "real" data*

MTTF (hours)	TDR	TODAY
Klystron	40,000	100,000
Modulator	100,000	500,000
Power supply	100,000	500,000
Electronics	100,000	500,000

10MW MBK vendor estimates

Solid-state with built-in redundancy

Solid-state with built-in redundancy

???

100 kh = 11.4 years

A simplified (analytical) approach


- Consider reliability due only to Main Linac RF system
 - ▶ Klystron - Modulator - Power supply - controls
- Failure of any one → failure of RF station
 - ▶ 39/26 cavities or 1275/850 MeV of energy

- MTTF of an RF station

$$\frac{1}{\text{MTTF}_{\text{RFS}}} = \frac{1}{\text{MTTF}_{\text{MKB}}} + \frac{1}{\text{MTTF}_{\text{MOD}}} + \frac{1}{\text{MTTF}_{\text{PS}}} + \frac{1}{\text{MTTF}_{\text{LLRF}}} = 62,500 \text{ hours}$$

I.e. one RF station will die every ~7 years on average

"Survival" curve of an RF station



Assuming simple exponential distribution $MTTF = 62.5$ khrs

Reliability


- Probability that something will run for a given time.
- What is the probability that **one or more RF stations** will fail before the next routine maintenance period (assumed $T = 14$ days = 336 h)
- Average rate of failure per period T :

$$\mathcal{R}_{fail} = N_{RFS} T / \text{MTTF}_{RFS}$$

		Baseline	Lumi Upgrade
Number of RF stations		186	279
ΔE per station	GeV	1.27	0.85
Final beam energy	GeV	253.5	
Overhead		1.4%	

$$\mathcal{R}_{fail} = \quad 1 \quad 1.5 \quad \text{for } T=14 \text{ days}$$


Probability of RF N_{fail} station failures



Poisson distribution with $\mu = 1.0$ (baseline, 1.5 upgrade) failures per 14 days

Reliability of ML with N_{spare} spare RF stations

Cumulative distribution function




Reliability is the probability that $N_{\text{fail}} \leq N_{\text{spare}}$

A more interesting question



- What is the reliability of operation for a given E_{CM} ?
- I.e. what is the probability that our beams will collider uninterrupted at E_{CM} for 14 days.
 - ▶ Due only to the ML RF
 - ▶ (Many other systems affect this reliability)
- Easy to figure out from our last plot, by *squaring the probability* (2 linacs!) and transforming the x-axis as

$$N_{spare} \rightarrow 2 \left[E_0 + \Delta E \left(N_{total} - N_{spare} \right) \right]$$

Reliability of E_{cm} operation due to ML RF





Reliability of E_{cm} operation due to ML RF




2% of 500 GeV

Impact of routine maintenance schedule




Impact of routine maintenance schedule

500.0 GeV operation
additional (spare) RF stations




	90%	95%	98%
14 days	2	2	3
21 days	3	3	4
28 days	4	4	5



	90%	95%	98%
14 days	1	2	2
21 days	2	3	4
28 days	4	4	5


GIGO revisited



Baseline



Final comments





Final comments

- Only considered Reliability due to RF stations in ML
 - ▶ Many other subsystems can cause downtime which will add to this.
 - ▶ All subsystems in ILC will need a high availability

Final comments

- Only considered Reliability due to RF stations in ML
 - ▶ Many other subsystems can cause downtime which will add to this.
 - ▶ All subsystems in ILC will need a high availability
- Reliability defined as probability that we are up until next maintenance period
 - ▶ Clearly if we lost all our spares we would just bring MD forward

Final comments

- Only considered Reliability due to RF stations in ML
 - ▶ Many other subsystems can cause downtime which will add to this.
 - ▶ All subsystems in ILC will need a high availability
 - Reliability defined as probability that we are up until next maintenance period
 - ▶ Clearly if we lost all our spares we would just bring MD forward
 - AVAILSIM calculated *Availability*
 - ▶ Includes *mean time to repair* and *mean time for recovery*.
-

Final comments

- Only considered Reliability due to RF stations in ML
 - ▶ Many other subsystems can cause downtime which will add to this.
 - ▶ All subsystems in ILC will need a high availability
 - Reliability defined as probability that we are up until next maintenance period
 - ▶ Clearly if we lost all our spares we would just bring MD forward
 - AVAILSIM calculated *Availability*
 - ▶ Includes *mean time to repair* and *mean time for recovery*.
-

Final comments

- Only considered Reliability due to RF stations in ML
 - ▶ Many other subsystems can cause downtime which will add to this.
 - ▶ All subsystems in ILC will need a high availability
 - Reliability defined as probability that we are up until next maintenance period
 - ▶ Clearly if we lost all our spares we would just bring MD forward
 - AVAILSIM calculated *Availability*
 - ▶ Includes *mean time to repair* and *mean time for recovery*.
 - Bottom line: does not look bad providing quoted MTTF can be achieved.
 - ▶ Very simplistic model for “educational” purposes only 😊
-