



# MDI Functional Requirements for the LOI



Tom Markiewicz/SLAC  
LCWS'08, UIC, Chicago  
17 November 2008



# Outline

- Context
  - **ILC Cost Reduction: Push-Pull**
  - **Aggressive EDR Timeline**
    - Above Ground Assembly
    - Need for a complete and cost-able design
  - **Current Climate: US P5 report, TDP-I, TDP-II, etc.**
- Proposed Philosophy:
  - **Minimal Functional Requirements for the LOI**
    - On\_Beam\_Detector-to-Machine Requirements
    - On\_Beam\_Detector-to-Off\_Beam\_Detector Requirements
  - **Collaboratively developed solutions and interfaces**
    - SiD-ILC-ILD & SiD-ILC-4th & ILD-ILC-4th
- Technical Solutions
  - **Sept-2007 IR Engineering Workshop**
  - **“Baseline” IR Design**



# US P5 Pre-Budget Cut Plan

Key	R&D	Construction	Operation
-----	-----	--------------	-----------

Roadmap for the Scenario with Constant level of Effort at the FY2007 Level													
	FY07	FY08	FY09	FY10	FY11	FY12	FY13	FY14	FY15	FY16	FY17	FY18	FY19
1. The Energy Frontier													
1.1 Tevatron collider													
1.2.1 Initial LHC													
1.2.2 SuperLHC--Phase 1													
1.2.3 SuperLHC--Phase 2													
1.3 ILC / Lepton Collider													


2009 LOIs

2016 "Construction" Start

My opinion:

- Relevant time horizon for this audience is LOI
- Simplify, generalize & do not be exclusionary

**Jan.09,2008**





# Names

- **MDI-D Common Task representatives**
  - ILD: Karsten Buesser (DESY) & Toshiaki Tauchi (KEK)
  - SiD: Phil Burrows (Oxford) & Marco Oriunno (SLAC)
  - 4<sup>th</sup>: Bill Ashmanskas (FNAL) & Alexander Mikhailichenko (Cornell)
- **GDE IR Integration**
  - BDS Leader: Andrei Seryi (SLAC)
  - BDS WP04 Integration Task Leaders:
    - Brett Parker (BNL) & Tom Markiewicz (SLAC)
- **IR Engineering Workshop Working Group Leaders**
  - A. Herve, J. Osborne, V. Kuchler, N. Mokhov, A. Enomoto, Y. Sugimoto, K. Tsuchiya, J. Weisend, M. Sullivan, D. Angel-Kalinin, T. Sanuki, H. Yamamoto



# Recent History & Future Goals

- 2007-Sept IR Engineering Workshop @ SLAC
  - **Work done in preparation & presented form rich picture of technical issues & possible engineering solutions**
- 2008-March ACFA-GDE meeting @ Tohoku, Japan
  - **The need to provide a clear set of ground rules to concepts so the MDI sections in their LOIs conform to agreed specifications leads to proposal of a “IR Interface Document” to accompany LOIs**
  - **Suggested that a paper summarizing IRENG07 “Baseline Design” be considered as draft of this “IR Interface Document” with authors those listed on previous slide**
- 2008-May-14
  - **1<sup>st</sup> and only “MDI Common Task” & GDE IR phone/webex meeting**
- 2008-June ECFA @ Warsaw
  - **First face-to-face discussions of how to proceed, identification of interface incompatibilities and plans for resolution**
  - **Agreement on role and text of EPAC paper**
    - Some fear of “signing off” on not-agreed-to baseline has been expressed
- 2008-Nov LCWS @ Chicago
  - **Draft of common “IR Interface Document”**
- 2009-March LOI
  - **Final interface document and LOIs with compatible MDI solutions**



# EPAC08 Paper

## **CHALLENGES AND CONCEPTS FOR DESIGN OF AN INTERACTION REGION WITH PUSH-PULL ARRANGEMENT OF DETECTORS – AN INTERFACE DOCUMENT\***

B.Parker (BNL), A.Herve, J.Osborne (CERN), A.Mikhailichenko (Cornell Univ.), K.Buesser (DESY), B.Ashmanskas, V.Kuchler, N.Mokhov (Fermilab), A.Enomoto, Y.Sugimoto, T.Tauchi, K.Tsuchiya (KEK), J.Weisend (NSF), P.Burrows (Oxford Univ.), T.Markiewicz, M.Oriunno, A.Seryi, M.Sullivan (SLAC), D.Angal-Kalinin (STFC), T.Sanuki, H.Yamamoto (Tohoku Univ.)

### *Abstract*

Two experimental detectors working in a push-pull mode has been considered for the Interaction Region of the International Linear Collider [1]. The push-pull mode of operation sets specific requirements and challenges for many systems of detector and machine, in particular for the IR magnets, for the cryogenics system, for alignment

The speed of push-pull operation is the first defining assumption. We set as the goal that hardware design should allow the moving operation, reconnections and possible rearrangements of shielding to be performed in a few days, or less than a week.

The range of detector sizes considered in the design include detectors with half size of 6-7 meters, performing



## Minimal Functional Requirements vs. evolving complete “Baseline” for LOIs

- “**IR Interface Document**” as a written minimal set of agreed on parameters to bound the MDI design for each concept
  - **Leave details for down the road and for the detector collaborations, especially if site dependent**
    - Eg. Deep versus shallow
  - **Suggest that detector-to-detector issues be worked out as 3 bi-lateral discussions, with BDS IR representation**
- **EPAC paper** draft is more of a complete set of engineering parameters to define IR region
  - **Changeable, but always as complete as possible**
  - **“Baseline IR Model”**





# Draft “Minimal Functional Requirements” Paper

I

ILC-Note-2009-nnn

March 2009

Version 0, 2008-11-16

## Functional Requirements on the Design of the Detectors and the Interaction Region of an $e^+e^-$ Linear Collider with a Push-Pull Arrangement of Detectors

B.Parker (BNL), A.Mikhailichenko (Cornell Univ.), K.Buesser (DESY), B.Ashmanskas (Fermilab), T.Tauchi (KEK), P.Burrows (Oxford Univ.), T.Markiewicz, M.Oriunno, A.Seryi (SLAC)

### *Abstract*

The Interaction Region of the International Linear Collider [1] is based on two experimental detectors working in a push-pull mode. A time efficient implementation of this model sets specific requirements and challenges for many detector and machine systems, in particular the IR magnets, the cryogenics and the alignment system, the beamline shielding, the detector design and the overall integration. This paper attempts to separate the functional requirements of a push pull interaction region and machine detector interface from the conceptual and technical solutions being proposed by the ILC Beam Delivery Group and the three detector concepts [2]. As such, we hope that it provides a set of ground rules for interpreting and evaluation the MDI parts of the proposed detector concept's Letters of Intent, due March 2009. The authors of the present paper are the leaders of the IR Integration Working Group within Global Design Effort Beam Delivery System and the representatives from each detector concept submitting the Letters Of Intent.

Draft will be posted on ILCDOC: <http://ilcdoc.cern.ch/>



# Push-Pull Detectors

## Fundamental Assumption for “Rapid” Switch


- QD0 moves with and is supported by detector
  - **$L^*$  optimized for each detector but  $3.5 < L^* < 4.5\text{m}$**
- QF1 stationary in tunnel or on pier at  $L^*_{\text{QF}}=9.5\text{m}$

## Passion-generating non-fundamental (imho) choices:

- Self-Shielding vs. Shield Walls vs. Access Restrictions
- Vertically-split endcaps vs. Non-split endcaps
- Platforms vs. rollers vs. airpads
- Crane capacity, shaft diameters, hall sizes

## Important but “merely” technical design:


- **cryo plant, cable plant, electronics volume & heat load etc.**






# Fix QF1 @ 9.5m, $L^*$ chosen by Detector Concept: Study Extraction Losses, Collimation & Optics Sensitivity

Nominal positions near IP for push-pull



Modified positions near IP: QDEX1 moves along with QD0, QF1 and QFEX2A are fixed at  $z = 9.5$  m and  $9.6$  m, respectively.






# QD0 CRYOSTAT @ IRENG'07

## 39cm constant radius

B. Parker et al,  
BNL

Key Detail Permitting Realization of Baseline Model  
is the Fully Engineered Compact Magnet Group  
Housing the Magnetic Elements of incoming &  
outgoing beams




- Overall dimensions of cryostat for QD0 designed for 4.5m L\*
- Cryostat extends 254mm beyond cold mass towards IP




# Detailed Cryo-engineering Based on Similar Magnets Built for HERA

## Local “Service Cryostat”

### Back End of QD0



B. Parker et al, BNL



Overall service cryostat dimensions



# Suggested Set of Minimal Constraints (imho)

- IP Beam parameter range set by ILC Project Mgmt.
- Hall width on beamline set by mandated  $9.5\text{m } L^*$  of QF
- Garaged position begins a fixed distance from beamline (15m?)
- Bare reinforced floor and bare walls in  $\pm 15\text{m}$  around beamline; all required services enter and leave with detector
- Radiation & magnetic environment in garage zone to be guaranteed at agreed on levels by the beamline detector using their chosen solution
- Time elapsed for push out/ pull consistent with chosen solutions
- QD0 support alignment range, accuracy, stability set by BDS
- QD0 cryo-connections respected during detector maneuvers
- Any other compatibility issues between concepts developed in up to 3 bilateral agreements
  - **Shielding interfaces, common cryo plants, etc.**





# Implication

---

Each concept's design should be evaluated by the IDAG  
(or IDAG appointed consultants)  
as to whether it complies with functional requirements






# Beam Parameters

- “Parameter Plane” of Beam Parameters at IP defined in RDR Table 2.1-2 as “Nominal”, “Low Charge”, “Large Vertical Beamspot” and “Low Power” each yield  $L=2E34/\text{cm}^2/\text{sec}$  but stress out a different part of the ILC
  - **Low Power & Large Y Spot need “Large Disruption” at IP to recover luminosity and resulting “disruption” blows up beam after collision more than “nominal” or “low charge”**
- Sad that we are still discussing this, but I know that the beam pipe radius at the IP, for certain concepts, and even that currently proposed extraction line diagnostics do not respect “Low Power” parameter set
- Need a “final word” on whether the parameter plane must be respected by the LOI designs




## Example: Current SiD Beam pipe is designed for ILC 500 GeV Nominal + 5 Tesla

500 GeV Nominal



500 GeV Low P



$e^+e^-$  pair envelope

For Low P: SiD beam pipe: 43mrad BP  $\rightarrow$  110 mrad and  $R = 1.2$  cm  $\rightarrow$  1.5 cm



## IR Hall Dimensions at the Beamline

- Stationary QF1 defines width of hall along beamline
  - **B field begins 9.5m and cryostat begins 9.24m from IP**
- Transverse distance from beamline to land “owned” by partner detector negotiable
  - **Working number 15m**
- Beam height above reinforced floor contentious as affected by
  - **Largest concept selected**
  - **Detector support & moving system selected**
  - **Working number 10m**



# Time Required for Detector Switch

Abandon the concept of “working numbers that concepts will try to satisfy” in favor of concept of “Figure of Merit based on a realistic plan” for concept evaluation

- **Push Out: clock for new detector starts when in garage**
- **Pull In Time: counts against beam-time allotted**

Obviously benefits everyone to minimize time

- **Credibility of push/pull concept**
- **Will determine # data periods/detector/year**
- **Shielding scheme preferred by concept**
  - Shielding that moves with the detector moves faster than a separate system but as long as time boundary respected concept should be free to choose what it needs
- **Time to reestablish luminosity assumed constant**
- **Re-Calibration time at expense of working detector**



# QD0 Constraints




Uncontroversial but pose engineering challenges

How to judge if constraint is met?

Does QD0 motion couple to FCAL position through chosen support scheme?

Z position of QD0 Cryostat	3.5-4.5m from IP
Detector axis	$\pm 1\text{mm}$ from line determined by QF1s
QD0 Alignment range	$\pm 2\text{mm}$
QD0 Alignment Accuracy	$\pm 200\mu\text{m}$ from line determined by QF1s
QD0 Stability	50nm, $\Delta(\text{QD}(e^+)-\text{QD}(e^-))$ , within 1ms pulse
# alignment DOF	5
Optical Access to QD0 ???	4 paths to each cryostat and the floor

# Example (SiD) of QD0 support with 5-DOF magnet mover system








# QD0 Service Cryostat

- Connected to QD0 via rigid pipes and assumed to rarely if ever be disconnected. Depending on shielding scheme, pipes must not provide a radiation leakage path
  - **Assumed to move with detector**
  - **Assumed to be limiting factor for detector access after connected and cold**
- Sized assuming 14W static and 1 W dynamic heat load at 1.9°K
- Connected to external cryo system via flexible line carrying single phase liquid He and low pressure He return gas



# Interference Between Movable Door & QD0 Service Cryostat







# Environment Imposed on Off-Beamline Detector

- Off-beamline detector “owned” space begins at agreed on distance (15m?) from beamline and users have complete access
- Static magnetic field < 100 Gauss (?)
  - **Speaks to amount of iron or degree of compensation for the iron free design**
  - **Equivalent requirement that field from the Off-Beamline detector must not distort On-Beam detector’s field more than  $10^{-4}$**
- Radiation
  - **Normal Operation and Accident Protection must be provided to the off-beamline region**
  - **Limit values regionally dependent & under discussion**



# Contentious Issues

## Probably only a partial list

### Shielding Walls versus Self-Shielding

- **As long as radiation requirements met it is up to concept to come up with their preferred shielding and or administrative controls (lack of access)**
- **Crane capacity, block storage location, etc. to be proposed by concept advocating given solution**
- **Time to demount consistent with agreed switch time**

### Common PACMAN Interface

- **To be developed in collaboration with other concepts**

### Air pads versus platforms versus rollers

- **Proposal is that a bare floor and walls must be left by the vacating detector**
  - All support services (power, cryo, water, gases,..) must be pulled in and out on flexible lines
- **Unless final two concepts agree on a different common solution**



## Self-shielding Example

Adjusting pacman to  
reduce dose below  
250mSv/hr

Desired  
thickness is in  
between of  
these two cases

18MW at  $s=-8\text{m}$ :

Pacman

Fe: 0.5m, Concrete: 2m

Fe: 1.2m, Concrete: 2.5m

dose at pacman external wall

1.2Sv/hr ( $r=3.5\text{m}$ )



6.5mSv/hr ( $r=4.7\text{m}$ )

dose at  $r=7\text{m}$

230mSv/hr



2.3mSv/hr

color scale is different in two cases








# Shielding the IR hall



Shielding the "4<sup>th</sup>" with walls




# Current SiD “PacMan” Rotating Hinged Design






# Disassembly of GLDc PACMAN for Push-Pull

- Plan view



- 3D view







Can ILD & SiD agree to a common solution for size/shape/motion of shielding permanently mounted to IR wall?






# Platform possibility for moving the detector







## Platform Free Example (SiD) for Moving the Detector







# FB Instrumentation & Vacuum Design and Push Pull



IRENG07 Workshop

Present vacuum requirements :

$P < 1\text{nT}$  in the BDS

$P < 100\text{nT}$  in the experimental region

- We may rely on the cryopumping from QD0
- We do not need extra pumps
- We do not need periodic bake out *in situ*.

Open point :

- The beam instrumentation required
- Shut-off valves



## Steps Forward

Concentrate on Minimal Functional Requirements

- As a group determine parameters and working values
- Three teams of 2 concepts plus BDS develop consistent conceptual solutions for interface and dictate design
  - **Begin this process immediately after LCWS Chicago**

Leave everything else not needed explicitly for the LOI:  
**garage sizes, crane capacities, shaft sizes, etc.**

to be filled in 'in the fullness of time'

This doesn't preclude maintaining several working models of what the entire IR complex would look like or investigating changes to fundamental assumptions (L\* completely outside the detectors, near-surface geology, etc.)




Backup Slides Follow



# Cryogenic Block Diagram in ILC IR Hall


What could be common has not yet been discussed



K.C. Wu, BNL




# Concept of single IR with two detectors






# IR integration

**Final doublet magnets are grouped into two cryostats, with warm space in between, to provide break point for push-pull**








14mr IR




BNL

Shield ON


Intensity of color represents value of magnetic field.



Shield OFF




Two Coils; Different Radii  
new force neutral antisolenoid



- Interaction region uses compact self-shielding SC magnets
- Independent adjustment of in- & out-going beamlines
- Force-neutral anti-solenoid for local coupling correction



# SC final double & its cryo system








# Present concept of cryo connection




## Vertical Layout for the Service Cryostat to QD0 Cryostat Transfer Line.

BROOKHAVEN  
NATIONAL LABORATORY  
Superconducting  
Magnet Division




B.Parker, et al





# L(L\*); achievements & sizes of hardware

## Quadrupole vibration:



On magnet top:



X:  $(0.4 \pm 0.1)$  nm

Y:  $(0.9 \pm 0.1)$  nm  
(0.3 nm on table top)

Z:  $(3.2 \pm 0.4)$  nm


without cooling water.

**R.Assmann et al, Stabilization with STACIS give ~10 reduction of tunnel floor vibration**




**P.Burrows et al, FONT3 demonstrated latency of 23ns, including 10ns of irreducible time-of flight**

**D.Urner et al, MONALISA interferometer system for ATF2 final doublet: space availability matters**




Monitoring Alignment & Stabilisation with high Accuracy





# Discussed an approach to CLIC IR stability


- Slower than  $1/L^*$  dependence of  $L_{um} \Rightarrow \uparrow L^*$
- Reduced feedback latency – several iteration of intratrain feedback over 150ns train
- FD placed on tunnel floor, which is ~ten times more stable than detector – easier for stabilization



- Not limited by sizes of stabilization system or interferometer hardware

- Reduced risk and increased feasibility
- May still consider shortened  $L^*$  for upgrade

# Back End of QD0



B. Parker et al,  
BNL

25.4mm (1in.)

Beam tube center  
line

75mm maximum flange  
diameter.