



Contribution ID: 188

Type: Oral presentation (remote)

High Gradient Testing of a Meter-Scale Distributed-Coupling C3 Accelerating Structures

Wednesday 10 July 2024 09:40 (20 minutes)

In this paper we report on the design, fabrication, tuning and high-power RF testing of the fundamental accelerating structure for the Cool Copper Collider (CCC). The results presented here cover the temperature range from room temperature to liquid nitrogen boil off: 20oC - 77 K

At room temperature, RT, with a N2 gas purge of 1 atmosphere, the CCC structure was tuned to a resonance frequency of $\langle f_o \rangle = 5.693\,420$ GHz, at 77K the structure tuned frequency is reported as $\langle f_o \rangle = 5.712\,057\,667$ GHz. The repeatability of the CCC structure to undergo both vacuum pump down and thermal cycles from RT to LN2 will be presented.

For the high-power RF testing the CCC structure was immersed in liquid nitrogen at the Radiabeam C-Band test facility. High Power RF breakdown data will be present along with our future experimental plans.

Apply for poster award

Primary authors: DHAR, Ankur (SLAC National Accelerator Lab); PALMER, Dennis (SLAC National Accelerator Laboratory / Stanford University); NANNI, Emilio (SLAC National Accelerator Laboratory); BROZENETS, Valery (SLAC National Accelerator Laboratory / Stanford University)

Presenter: PALMER, Dennis (SLAC National Accelerator Laboratory / Stanford University)

Session Classification: Normal conducting RF

Track Classification: Accelerator: Normal Conducting RF