

# SRF programs towards High-Q/High-G cavities in IJCLab


Akira Miyazaki, Mohammed Fouaidy, Nicolas Gandolfo, David Longuevergne,

Guillaume Olry, Mael Vannson, Lê My Vogt

CNRS/IN2P3/IJCLab Université Paris-Saclay


Matthieu Baudrier, Enrico Cenni, Fabien Eozénou, Grégoire Jullien, Luc Maurice

CEA/IRFU/DACM Université Paris-Saclay





# Introduction : Instances around SUPRAtech



Credits :  
J.L. Biarrotte



# Introduction : History summary and series production

Prototyping Phase

Series production

R&D



**Spiral2** : Integration and test of 7 cryomodules




**ESS** : - preparation & testing of cavities, couplers and tuners  
- Integration of 14 cryomodules




**LHC** : Calibration of all Cernox thermal sensors (> 6000 units)



**EU-XFEL** : Preparation and power testing of 800 couplers



**MYRRHA** : - preparation & testing of 60 couplers and tuners



**PIP-II** : Testing of 33 Spoke cavities




# Low- $\beta$ cavities for protons & heavy ions $\rightarrow$ collider cavities



352 MHz

FCC/PERLE cavities (800 MHz)

88 MHz







ILC cavities (1.3 GHz)

352 MHz







325 MHz



# Next future colliders: priority in Higgs boson


arXiv:1407.2133








# Energy Recovery Linac (ERL)


Linear colliders



Circular colliders



Injector



	FCCee/CEPC	ILC	HE ILC	CCC	HE CCC	CLIC	HE CLIC	CERC	ReLiC	HE ReLiC	ERLC	XCC	LHeC/FCCeh
RF Systems													
Cryomodules													
HOM detuning/damp													
High energy ERL													
Positron source													
Arc&booster magnets													
Inj./extr. kickers													
Two-beam acceleration													
Damping rings													
Emitt. preservation													
IP spot size/stability													
High power XFEL													
e <sup>-</sup> bunch compression													
High brightness e <sup>-</sup> gun													
IR SR and asymm.quads													

JINST 18 P05018 (2023)





# PERLE project at IN2P3/IJCLab

Ultimate goal of PERLE: first multi-turn ERL designed to operate at 10 MW (20 mA, 87→250→500 MeV)

→ A hub to explore a broad range of accelerator phenomena and to validate technical choices improving accelerators for future energy and intensity frontier machines

Target Parameter	Unit	Value
Injection energy	MeV	7
Electron beam energy	MeV	250 / 500
Average beam current	mA	20
Bunch charge	pC	500
Duty factor		CW



## For FCC/PERLE


Duty cycle  
=100%




Extremely high-Q at relatively high gradient in large cavities (800 MHz)

## For ILC250

Duty cycle  
<1%



Extremely high gradient with relatively high-Q in a large # of cavities (~8000)









# high-Q / high-G cavities in the world


## 300C baking @ IHEP




## 120C baking @ CEA-Saclay



## 2N0 doping at 800C @ LCLSII




- 300C baking or N-doping seems like the best option for FCC/PERLE
- 120C or 2-step baking for higher gradient  $\rightarrow$  ILC
- **Clean vacuum baking furnace** is key in this research domain




- Vacuum furnace originally used for 600C annealing of ESS spoke cavities
- A cryogenic pump, pure Ar for purging etc
- New R&D with DESY 1.3 GHz cavities

M. Fouaidy et al., IEEE  
 Transactions on Applied  
 Superconductivity, vol. 28,  
 no. 4, pp. 1-6 (2018)



# 1<sup>st</sup> test is always far from ideal (CV1 at CEA Saclay on June 18 2024)





- 1<sup>st</sup> cooling down after long shutdown
- T-sensor at the bottom broken





# 1<sup>st</sup> test results



- The mid-T baked cavity showed significantly high residual resistance  $\Delta R_{res} > 46 \text{ n}\Omega$   
→ Is it due to contamination of furnace/cavity or magnetic field effect?



# Magnetic field sensitivity (1.3 GHz cavities)




$$H_{ext} \sim 25 \text{ mG} = 2.5 \mu\text{T}$$


Not yet optimized

$$\rightarrow \Delta R_{res} \sim S H_{ext} = 50 \text{ n}\Omega$$

## JLab





## KEK



$$S \sim 2 \text{ n}\Omega/\text{mG}$$



## Compare to JLAB result at 2 K: 25 mG case



- We could explain the degradation of Q due to non-optimized magnetic shield and high sensitivity to trapped flux in mid-T baked cavities  
→ Improving magnetic shield and installing magnetic field mapping at CEA after summer



# Conclusions

- **IJCLab has been a world-leading laboratory of SRF cavities for proton / heavy ion linear accelerators**
  - R&D of Spiral2, ESS, MYRRHA, PIP-II cavities are coming to the final phase
  - Contributions to collider projects has been in beam dynamics and nanobeams (ATF), RF couplers (Eu-XFEL), temperature sensors (LHC), etc
- **IJCLab is expanding R&D activities of SRF cavities towards future colliders**
  - FCC / PERLE 800 MHz cavities: super high-Q
  - ILC 1.3 GHz cavities: super high-G
- **Advanced heat treatment is the key R&D subject**
  - IJCLab is equipped with a clean vacuum furnace originally used for the ESS spoke cavity project
  - Mid-T baking for super high-Q
  - 1<sup>st</sup> mid-T baked results in 1.3 GHz cavity → studies on-going
- **Future prospects**
  - 2<sup>nd</sup> test with improved magnetic field at CEA (July 18), test at STF in KEK (October)
  - Heat treatment of the 800 MHz prototype cavity
- **Collaborations**
  - ERL collaboration with KEK via FJPPL
  - FCC: collaboration with CERN/FNAL
  - PERLE: collaboration with CERN/JLAB



backup






## Open questions

- **Magnetic field sensitivity**
  - N-doping/mid-T bake makes cavities sensitive to trapped magnetic fields
  - Factor 10 better magnetic shield may be necessary
  - Flux expulsion technique with higher thermal gradient
  - Advantage of mid-T baking is based on a compromise between ultimately high-Q and realistic trapped flux level in a cryomodule
- **EP vs BCP**
  - EP + mid-T bake has been studied intensively
  - EP is mandatory for very high gradient but may not be for high-Q at decent field
  - BCP is simpler and less expensive
  - The limited number of tests have been performed for BCP + mid-T baking → results are somewhat contradictory
- **Low-T bake could also be an option for FCC/PERLE**
  - Not enough margin even in the best case but probably more conservative




# List of the different recipes


## xNy doping



## N-infusion



## 2-step baking (1.3 GHz)



## Mid-T baking

