

Strategy for cavity R&D towards an upgrade of the European XFEL - current performance and the need for a new specification

LCWS 2024

Lea Steder, Detlef Reschke

with slides / input from Hans Weise, Julien Branlard, Nick Walker,
for the DESY SRF team


July 10th, 2024

HELMHOLTZ




Introduction

The European XFEL Accelerator : one RF station




- 10 MW klystron to power 32 cavities
- one accelerating field RF control FB loop
- remote frequency tuning (motor / piezo) / cavity
- remote phase and external coupling tuning / cavity
- average coupler peak power 102 kW (140 kW) for low (high) runs
- average gradient 18.5 MV/m (22.5 MV/m) for low (high) runs
- average detuning +/- 10 Hz
- average $Q_{ext} = 4.6e6$ average $Q_0 = 1e10$

R&D towards HDC




R&D for the High Duty-Cycle program (i.e. cw and long pulse)

Motivation




→ TODAY


High Duty Cycle (HDC)




original CW upgrade proposal (canonical upgrade)



original CW upgrade proposal (canonical upgrade)




original CW upgrade proposal (canonical upgrade)



requirements for hdc optimized modules: HDC and pulsed

Preliminary list

- to be emphasized:
requirement for **high energy (pulsed) mode and hdc/cw mode in one linac**
- performance requirements:
 - gradient $E_{acc} > 20 \text{ MV/m}$
 - quality factor $Q_0(\sim 20 \text{ MV/m}) \geq 3 \cdot 10^{10}$
 - significantly **lower (no) field emission** than existing cryomodules
 - PED conformity: no annealing above $800 \text{ }^\circ\text{C}$
- as **less as practicable modifications** to EuXFEL cavity and cryomodule
→ first ideas, but design not started
- preliminary: Use existing EuXFEL-coupler design with thicker Cu coating
- **new cw compatible 3.9 GHz cavities** required
→ preliminary base: follow available 3rd harmonic cavity and module designs



R&D for the High Duty-Cycle program (i.e. CW and long pulse)

accelerator modules

- high Q_L operation
- cw diagnostics and resonance control
- studies towards operating series cryomodules in CW

s.c. cavities

- renewal of DESY XFEL cavity specification incl. PED
- extensive R&D using a large number of single cell cavs
- new/optimized treatment recipes

s.c. electron gun

- SRF gun as the source
- SRF injector design
- Ts4i



R&D for the High Duty-Cycle program (i.e. CW and long pulse)

accelerator Modules

- high Q_L operation
- cw diagnostics and resonance control
- studies towards operating series cryomodules in CW

s.c. cavities

- renewal of DESY XFEL cavity specification incl. PED
- extensive R&D using a large number of single cell cavs
- new/optimized treatment recipes (industrialization!)

s.c. electron gun

- SRF gun as the source
- SRF injector design
- Ts4i

W. Sipek

VALID DOCUMENTS
FOR THE
SERIES MECHANICAL
FABRICATION
OF
SUPERCONDUCTING 1.3GHZ
CAVITIES
FOR THE
EUROPEAN XFEL

(XFEL/001)

REVISION B / JUNE 23, 2009

SERIES SURFACE AND
ACCEPTANCE TEST PREPARATION
OF SUPERCONDUCTING CAVITIES
FOR THE EUROPEAN XFEL

(XFEL/A - D)

REVISION B / JUNE 30, 2009



EDMELN: 0000000141900 Rev B Ver 10 Status: Approved Date: 20.06.2009

1 / 71




EDMELN: 0000000141900 Rev B Ver 2 Status: Approved Date: 30.06.2009

towards an updated DESY XFEL spec

European XFEL uses 800 cavities ordered in 2010; the tendering started 15+ years ago

- the often-called DESY specs were the **role model** for LCLS-II (HE), SHINE et al.
- **PED certification** was/is a major issue for DESY, a renewal is a must in order to prepare for an EuXFEL upgrade cavity ordering
- basis for tendering of **ten new nine-cells** (early 2025)
- **lessons learned** from EuXFEL, LCLS-II (-HE), SHINE production to be included
- **company experience** counts
- **next generation of experts** to be trained (mix of new and experienced colleagues; new roles)
- new and **optimized surface treatment** recipes to be finalized; decision for next EuXFEL ordering



“test piece” production for vendor qualification

progress of the updated DESY XFEL spec


a team effort

- **one consistent document**
 - includes lessons-learnt of XFEL-production (e.g. not well-defined dimensions for He-tank brackets)
 - **vendor independent workflow** description
 - **bellow unit at He-tank simplified**
 - additional **acceptance level for a R&D phase** before He-tank integration
 - surface treatment:
 - **“final EP“ as initial surface treatment** only
 - **cold EP** process adopted
 - Mid-T treatment during R&D phase at DESY
 - emphasis kept on **well-defined processes** during whole production incl. **on-site visits**
- ### EuXFEL specification 2009
- several separate documents (fabrication, treatments, ...)
 - modifications during the tender process, adaption to infrastructure at vendor and during series fabrication
 - delivery of tank-integrated cavities
 - no experience in industry with large-scale cavity surface treatment
 - included “Flash-BCP“ as final surface treatment

progress of the updated DESY XFEL spec

a team effort

- **one consistent document**
- includes lessons-learnt of EuXFEL-production (e.g. not well-defined dimensions for He-tank brackets)
- **vendor independent workflow** description
- **bellow unit at He-tank simplified**
- additional **acceptance level for a R&D phase** before He-tank integration
- surface treatment:
 - **“final EP“ as initial surface treatment** only
 - **cold EP** process adopted
 - Mid-T treatment during R&D phase at DESY
- emphasis kept on **well-defined processes** during whole production incl. **on-site visits**



progress of the updated DESY XFEL spec


a team effort

- **one consistent document**
 - includes lessons-learnt of XFEL-production (e.g. not well-defined dimensions for He-tank brackets)
 - **vendor independent workflow** description
 - **bellow unit at He-tank simplified**
 - additional **acceptance level for a R&D phase** before He-tank integration
 - surface treatment:
 - **“final EP“ as initial surface treatment** only
 - **cold EP** process adopted
 - Mid-T treatment during R&D phase at DESY
 - emphasis kept on **well-defined processes** during whole production incl. **on-site visits**
- ### EuXFEL specification 2009
- several separate documents (fabrication, treatments, ...)
 - modifications during the tender process, adaption to infrastructure at vendor and during series fabrication
 - delivery of tank-integrated cavities
 - no experience in industry with large-scale cavity surface treatment
 - included “Flash-BCP“ as final surface treatment

cavity treatment towards hdc operation

focus on mid-T heat treatment

- **refurbished UHV niobium retort furnace** is used to anneal cavities up to 800°C.
- loading of the furnace is done directly in the DESY ISO4 clean room i.e. **extremely clean** environment
- single-cell cavities / **pairs of single-cell** / 9-cell cavities can be treated.
- mid-T treatment in UHV at 250-350°C (rem.: so far all studies without additional gas inlet - which is possible)



oxygen diffusion length as key parameter

huge DESY mid-T campaign

mid-T campaign

- all 19 treatments on single-cell cavities after "reset"
- 5 treatments on large grain (LG) cavities
- wide range for T: 250°C to 350°C and t: 3h to 20h
- use of calculated oxygen diffusion length l for classification

DESY mid-T workflow

- "reset": 800°C anneal / short, cold EP (20 μm)
- HPR & assembly
- baseline vertical test
- mid-T treatment with different temperatures and durations (T, t)
- HPR & assembly
- vertical test (VT)

Cavity	Nominal treatm.	l (nm)	
1RI04	<3h <250°C	234	Fig. 9 short l
1DE12	<3h 250°C	249	
1DE26 (LG)	<3h <300°C	501	Fig. 10 medium l
1RI02	20h 250°C	512	
1DE04	<3h <300°C	528	
1DE03	<3h <300°C	537	
1DE07	20h 250°C	560	
1DE07 18xHPR	<3h <300°C	641	
1AC07 (LG)	<3h <300°C	697	
1AC03 (LG)	<3h <300°C	789	Fig. 4
1AC02	3.25h <325°C	865	
1DE19	4.5h <335°C	1248	Fig. 11 long l
1RI06 (LG)	20h 300°C	1735	
1RI07 (LG)	3h <350°C	1806	
1DE11	3h <350°C	1839	
1DE17	20h 300°C	2039	
1RI01	3h 350°C	2354	
1AC02	3h \geq 350°C	2568	
1DE12	3h >350°C	2655	


Table 1: Cavity treatments sorted by calculated diffusion length l and grouped according to l .

quality factor enhancement and anti-Q₀-slope

special characteristics of mid-T heat treated cavities

standard EuXFEL recipe vs mid-T heat treatment

- significantly enhanced quality factors
- **anti-Q-slope**
- lower gradients
- **partially stopped** to avoid quenching




very low BCS surface resistance

special characteristics of mid-T heat treated cavities

standard EuXFEL recipe vs mid-T heat treatment


- significantly enhanced quality factors
- anti-Q-slope
- lower gradients
- $R_S(T,B) = R_{BCS}(T) + R_{res} + R_{flux}(B)$
- **lower R_{BCS}**
- **but** partially higher R_{const}



sometimes degradation after quenches

special characteristics of mid-T heat treated cavities

- significantly enhanced quality factors
- anti-Q-slope
- lower gradients
- $R_S(T,B) = R_{BCS}(T) + R_{res} + R_{flux}(B)$
- lower R_{BCS}
- **but** partially higher R_{const}
- 8 of 19 cavities **degrade after first quench**
 - unclear origin
 - **healing** via thermal cycling to 30 K



correlation of performance to oxygen diffusion length missing



gap between 900 and 1700 nm to be filled

quality factor Q_0

- flat distribution over diffusion length
- only low performer deviating
- LG cavities on upper edge

maximal E_{acc}

- spread between 20 and 35 MV/m
 - tendency at higher length towards larger gradients?





not much room for optimization

trends in resistances cancel each other

R_{BCS} and R_{const}

- LG and low performer excluded
- opposing trends
- LG cavities profit from low R_{const}




not much room for optimization

trends in resistances cancel each other

R_{BCS} and R_{const}

- LG and low performer excluded
- opposing trends
- LG cavities profit from low R_{const}




reminder

- $R_S = R_{BCS} + R_{const}$, $Q_0 \sim 1/R_S$

sensitivity to magnetic flux trapping is a challenge

B-mapping studies show large impact of mid-T heat treatment



- definition: $S = \frac{\Delta R_S}{B_{\text{trap}}}$
- R_S measured via Q_0 with and w/o applied magnetic field (10 μT)
- B_{trap} obtained via B-mapping system
 - FG (1DE03) and LG (1DE26) cavity with medium I (< 3h, < 300°C)
 - measurements at KEK



sensitivity to magnetic flux trapping is a challenge

B-mapping studies show large impact of mid-T heat treatment

- definition:
$$S = \frac{\Delta R_S}{B_{\text{trap}}}$$
- R_S measured via Q_0 with and w/o applied magnetic field (10 μT)
- B_{trap} obtained via B-mapping system
 - FG (1DE03), LG (1DE26) cavity with medium ℓ (< 3h, < 300°C)
 - measurements at KEK
- increase in sensitivity: factor 4 - 5!
 - independent of cavity material
- magnetic environment - also in accelerator - very important
 - flux trapping has to be avoided
 - otherwise Q_0 will drop significantly
- more studies to come for better statistics with wider range of ℓ



summary

- (smooth EuXFEL linac operation => aiming for three 9s linac availability)
- **broad R&D towards** an hdc upgrade of the European XFEL started – **pulsed and hdc operation**
- good progress of **reworked spec** for cavity production
- **excellent furnace and cleanroom** infrastructure as well as sufficient single-cells available
- R&D focus on **mid-T treatment**: **Arxiv publication** with more details this week
 - **reproducible and very promising results** on single-cells
 - **high sensitivity S** to magnetic flux is a challenge
 - next: transfer to nine-cells

Funding by the European XFEL R&D program and the Helmholtz MT ARD program acknowledged

thank you for your attention

Many thanks to all colleagues from different groups at DESY who have contributed to these results.

Contact

Deutsches Elektronen-
Synchrotron DESY

www.desy.de

Lea Steder

lea.steder@desy.de

+49 (0)40 8998 3828

Detlef Reschke

detlef.reschke@desy.de

+49 (0)40 8998 2772