

Report on ATF2 Third Project Meeting

ATF2 Magnet Movers

ATF2 Q-BPM Electronics

ATF2 Magnet Mover progress

- 10 crates (24 movers) and electronics at ATF
- Four movers and electronics sent to France for testing on CERN IP table.

ATF2 Magnet Movers

- SLAC is providing all electronics to operate movers
- Movers require space for 17 chassis taking a total of 55 rack units plus one camac crate with 15 empty slots.
- Optimum layout will require three racks loaded something like this .


15 slots required for camac crate:

2 magnet mover modules
2 ADC modules
11 LVDT modules

Magnet mover chassis	m a g n e t m o v e r	Magnet mover chassis
Magnet mover chassis		Magnet mover chassis
Magnet mover chassis	Camac crate	Magnet mover chassis
Resistor chassis	Dc power supply	Resistor chassis
Resistor chassis	Dc power supply	Resistor chassis
Resistor chassis	Resistor chassis	Resistor chassis
Resistor chassis		Resistor chassis


30mm thick iron plate
to fix magnets

Concrete block




10mm thick iron plate
to fix electronics boxes for BPM

Not scaled !




**Type 3
(3 blocks)**




Type 3 (3台)
 高エネルギー加速器研究機構
 S = 1/10
 菅原 2006.11.01

**Type 4
(14 blocks)**



<Top View>




<Side View>


Type 4	(14台)
高エネルギー加速器研究機構	
S = 1/10	
菅原	2006.11.01

Electronics Overview


- Downmix ~6426 MHz to 26 MHz
- 2ch/box
- Single LO input. Level 3dbm
- Forward and reverse calibration inputs. Level from 0 to 20dbm
- DC input 5.8 W at 8V
- Analog outputs monitor LO power, Calibration power and board temperature.
- Output to 14-bit 100 MHz SIS digitizers



Performance Results



Crosstalk




Heavily saturated BPM pulse in channel 1 of electronics

Solid line is the response in channel 2 with no input (terminated)


~60 dB channel-to-channel isolation on same board

Resolution




Performance in Saturation


- Digitizer limits +/- 1 V



Read Back Results



Temperature data sample
from 14-Dec-2006
(NanoBPM shift running
ATF2 electronics)



Test ramp using temperature
control enclosure at ESB


OPERATION

- First pulse calibration
 - Provide a rapid method of obtaining relative x and y positions with the correct sign from each QBPM. Beam only required to be through the first QBPM and Reference cavity.
 - Requires careful setup and measuring of Z positions of QBPMs and REF cavities. Phase advance of RF and IF cable plant must also be measured or adjusted.
 - All this is to be done before beam operation.

Operation

First Pulse Calibration

Difference in z position results in non-integer or **delta phase**



Set equal, or precisely determine the LO phase and signal path for each BPM

The distance between the reference cavity and a given BPM produces a noninteger cycle of 6426MHz.
This is the phase difference between the REF cavity and the BPM signal phase (**delta phase**).

Calibrate one BPM with corrector ::

This BPM's signal minus its BPM **delta phase** is the **signal phase** for a positive (x and y) orbit through BPM
For each downstream BPM, correct its signal with its **delta phase** and compare with the **signal phase**.

A corrected BPM signal that is 0-179° from the **signal phase** indicates a positive(x and y) orbit in the BPM.

Relative amplitude of the position can be produced scaling the digitizers 14bits to ±10mm.

- **Mover Calibration**

- Use X and Y movers to perform absolute calibration.
- Use DDC analysis to obtain I and Q phases and produce calibrations. Corrector scans for QBPMs with no movers?
- Need to improve program to improve response time, and handle saturated signal conditions



Installation

- Electronics and hardware
- Software development


Electronics and hardware

- Components

- 38 down mix boxes
- VME 64x crate
 - VME cpu type yet to be determined. Support vxWorks or RTEMS
 - 10 SIS digitizers (80 channels).
 - 2 analog read back digitizers (VMIC 3122)
- DC power supply, cables and distribution chassis
- Analog read back cables and patch panel system
- 20 MHz signal cables patch panel and jumper cables.
- BPM magnet mover test bed.
 - ATF2 quad with ,QBPM on magnet mover in ATF extraction line.
- RF infrastructure (see next)
 - LO/CAL locking system
 - LO/CAL distribution system
 - 2 Watt 6444MHz distribution amp, couplers and splitters



RF Infrastructure in tunnel



Software development

- EPICS IOC for VME control.
- Single pulse readout.
- Magnet mover calibration.
- Position calculation. DDC analysis for normal and saturated BPM signals.
- Calibration tone amplifier gain monitoring.
- LO, CAL power and temperature monitoring.
- EPICS communication with ATF control system.

Delivered

- 38 Down mix boxes
- 10 SIS modules
- 2 Analog input modules
- DC power distribution
- Analog distribution
- LO locking box. (Tested during Dec. run) Still need to add CAL tone locking system

Still to go...

- Need detailed information on rack locations, penetrations into the housing, and cable routing in the tunnel before finalizing cable plant for LO and CAL systems
- Select VME crate controller
 - RTEMS or vxWorks
- Software development
- Test bed setup. Ready for spring '07 testing.
 - Test first pulse and mover calibration schemes

EXTRA: Detailed RF Dist. Path

