

ILC Damping Rings R&D Plan

**Summary of Work Packages,
Resource Requirements and Deliverables**

Revision 3: 28 March 2007

The R&D Objectives identified as “Very High Priority” are contained within the following Work Packages:

S3 WBS	Work Package	S3 WP Manager(s)
2.1.1	Lattice Design	Mike Zisman
2.1.4	Low-Emittance Tuning	Andy Wolski
2.2.1	Impedance-Driven Single-Bunch Instabilities	Marco Venturini
2.2.3	Electron Cloud	Mauro Pivi
2.2.4	Ion Effects	Mauro Pivi & Marco Venturini
3.5.1	Fast Injection/Extraction Kickers	Tom Mattison

Staff Effort (FTE; excludes operational support for Facilities)

S3 WBS	2007	2008	2009	2010
2.1.1	??	??		
2.1.4	7.5	7.5		
2.2.1	4.5	4.5		
2.2.3	8.5	8.5		
2.2.4	6.0	4.0	4.0	
3.5.1	8.0?	8.0?		

M&S (US\$k; excludes operating costs for Facilities)

S3 WBS	2007	2008	2009	2010
2.1.1	0	0		
2.1.4	250	250	100	100
2.2.1	0	0		
2.2.3	730	920		
2.2.4	200?	200?		
3.5.1	1,000?	1,000?	1,000?	

Facilities

S3 WBS	
2.1.1	None required
2.1.4	CesrTA, ATF, ALS, APS
2.2.1	None required
2.2.3	CesrTA, PEP-II, KEKB, DAΦNE, (LHC)
2.2.4	CesrTA, ATF
3.5.1	ATF, FNAL-A0, DAΦNE, (CesrTA)

Key Deliverables (of Very High Priority Objectives)

Objective 2.1.1.1: Lattice design for baseline positron damping ring

- *Deliverables to be defined.*

Objective 2.1.1.2: Lattice design for baseline electron damping ring

- *Deliverables to be defined.*

Objective 2.1.4.3: Demonstrate < 2 pm vertical emittance

- Demonstration that the vertical emittance goal of 2 pm in the damping rings is achievable.
- A range of essential information and data for improving the completeness of low-emittance tuning simulations, for optimising low-emittance tuning techniques (Objective 2.1.4.1), and for specifying design requirements for the lattice, coupling correction schemes (2.1.4.5), instrumentation and diagnostics performance, and survey and alignment accuracy (Objective 2.1.4.2).

Objective 2.2.1.2: Characterization of single-bunch impedance-driven instabilities

- Estimates of the instability thresholds.
- Characterization of the beam dynamics associated with the instability.
- Feedback and guidance on the specifications and technical designs for the lattice and vacuum chamber components.

Objective 2.2.3.1: Characterize electron-cloud build-up

- Detailed and reliable description of electron cloud density in various sections (wiggler, bends, quadrupoles, field-free) of the positron damping ring, under a variety of possible conditions. The conditions will include ranges of beam parameters, and specifications for the vacuum system, and for the wiggler and other magnets.

Objective 2.2.3.2: Develop electron-cloud suppression techniques

- Technical specifications for techniques to be used to suppress build-up of electron cloud in the positron damping ring, consistent with aperture and impedance requirements.
- Guidance for the design of the vacuum chamber material and geometry (Objective 3.1.1.1), and for the technical designs for principal vacuum chamber components (Objective 3.1.1.2).

Objective 2.2.3.3: Develop modeling tools for electron-cloud instabilities

- Support for the determination of electron-cloud instability thresholds (Objective 2.2.3.4) for the positron damping ring.
- Guidance for the specification of the secondary electron yield as input for the characterization of an electron-cloud build-up (Objective 2.2.3.1).

Objective 2.2.3.4: Determine electron-cloud instability thresholds

- Prediction of the electron cloud driven single-bunch instability threshold for the positron damping ring.
- Specification of the maximum permissible cloud density in the positron damping ring, as a target for the development of mitigation techniques (Objective 2.2.3.2).

Objective 2.2.4.1: Characterize ion effects

and Objective 2.2.4.2: Specify techniques for suppressing ion effects

- Experimental validation of theoretical models and simulation tools for the fast ion instability.
- Indication of machine design parameters (including bunch filling patterns, lattice optics, feedback and vacuum specifications) capable of delivering a beam with the required quality and stability without limitations from ion effects.
- Guidance for optimization of design of vacuum and feedback systems, and optimization of the optics design, to avoid limitations from ion effects.

Objective 3.5.1.1: Develop a fast high-power pulser for injection/extraction kickers

- *Deliverables to be defined.*

DRAFT

Work Package 2.1.4 Low Emittance Tuning

Work Package Coordinator: Andy Wolski

Potential Investigators

ANL

Louis Emery
Vadim Sajaev
Aimin Xiao

Cockcroft Institute

James Jones
Kosmas Panagiotidis
Andy Wolski

Cornell

Scott Chapman
Don Hartill
Richard Helms
Mark Palmer
David Rubin
Maury Tigner

KEK

Kiyoshi Kubo
Junji Urakawa

LBNL

Gregg Penn
Ina Reichel
Marco Venturini
Mike Zisman

Oxford University

Armin Reichold
David Uner

SLAC

Yunhai Cai

Summary of Required Resources

Objectives

S3 WBS	Objective	Priority
2.1.4.1	Develop strategies for low-emittance tuning	High
2.1.4.2	Specify requirements for survey, alignment and stabilization	High
2.1.4.3	Demonstrate < 2 pm vertical emittance	Very High
2.1.4.4	Specify support schemes for damping rings magnets	High
2.1.4.5	Specify orbit and coupling correction scheme	High

Staff Effort (FTE; excludes operational support for Facilities)

S3 WBS	2007	2008	2009	2010
2.1.4.1	2.0	2.0		
2.1.4.2	0.5	0.5		
2.1.4.3	2.0	2.0		
2.1.4.4	2.0	2.0		
2.1.4.5	1.0	1.0		

M&S (US\$k; excludes operating costs for Facilities)

S3 WBS	2007	2008	2009	2010
2.1.4.1	0	0		
2.1.4.2	0	0		
2.1.4.3	450	450		
2.1.4.4	0	0	100	100
2.1.4.5	0	0		

Facilities

Experimental studies at CEsrTA, ATF, ALS and APS are required to complete Objectives 2.1.4.1, 2.1.4.2 and 2.1.4.3. Results from these studies are also required for Objectives 2.1.4.4 and 2.1.4.5.

Objectives

Objective 2.1.4.1: Develop strategies for low-emittance tuning

High Priority

The baseline parameters for the ILC specify an extracted normalized vertical emittance of 20 nm from the damping rings; this corresponds to a geometric emittance of 2 pm at the damping rings' energy of 5 GeV. Although there is a budget of 10 nm normalized emittance growth between the damping rings and the interaction point, any increase in the vertical emittance extracted from the damping rings will have a direct adverse impact on the ILC luminosity.

There are several effects that contribute to vertical beam emittance in storage rings, but the dominant ones in electron rings (as will be the case for the ILC damping rings) are related to misalignments of the quadrupole and sextupole magnets. Achieving a vertical emittance of the order of a few picometers will depend on three factors:

- appropriate design of the lattice to minimize sensitivity of the vertical emittance to magnet alignment errors;
- precise initial alignment of the magnets (to within tens of microns);
- rigorous and systematic compensation of the residual alignment errors using beam-based techniques.

The lowest vertical emittance achieved in any existing storage ring is 4.5 pm in the KEK-ATF [1]. Some other storage rings, for example the Advanced Light Source at LBNL, have approached this value [2]. The principle difficulty in low-emittance tuning lies in determining the coupling sources with sufficient precision to allow an effective correction to be applied: in the picometer emittance regime, magnet misalignments of a few microns are significant. A further difficulty is that with such low emittances, the beam size is generally just a few microns, and the instrumentation required to make precise beam size measurements in this regime is still under development. This means it is not possible to apply coupling corrections based on simple direct measurements of beam size; instead, more sophisticated approaches are required.

Generally, the first step in minimizing the vertical emittance involves correcting the orbit and dispersion using steering magnets. The second step requires optimum settings to be determined for the corrector magnets, such as skew quadrupoles, used to compensate residual alignment errors. This can be done in a variety of ways: one method that has been applied with some success at the ATF is to minimize the orbit response in one plane (horizontal or vertical) to deflections applied with a small number of carefully selected steering magnets in the other plane (respectively, vertical or horizontal) [3]. Alternative methods include use of orbit response matrix analysis [4], model independent analysis [5] and phase advance analysis [6]. For some of these techniques, efforts to apply them to tuning for vertical emittance in the picometer regime have only recently begun.

Despite considerable effort over several years, the target emittance of the damping rings has not been achieved in any existing facility, and a thorough study of low-emittance tuning techniques is therefore necessary. Such a study should include optimization and comparison of existing techniques, as well as the development of new approaches. The work should be undertaken over the timescale of the

Engineering Design Report, since the results are likely to have some impact on a number of aspects of the damping rings design and specifications, including:

- Lattice design. It is often necessary to make compromises in the design between competing requirements. For example, a particular working point in tune space might be optimum from point of view of dynamic aperture, but poor in terms of the sensitivity of the lattice to alignment errors.
- Alignment specifications. The specifications on the survey alignment of the magnets are presently based on studies that are not completely rigorous, and are known to be demanding, particularly for the baseline configuration in which both damping rings are located in a single tunnel. Improving the effectiveness of coupling correction methods could ease the requirements on the survey alignment.
- Instrumentation and diagnostics. Experience at the ATF has emphasized the critical role of the performance of the instrumentation (particularly the beam position monitors, and beam size diagnostics) in achieving low vertical emittance. The specifications for the instrumentation will depend on the techniques proposed for low emittance tuning. Different techniques have different requirements in terms of functionality (e.g. for turn-by-turn measurements from the BPMs) and performance.

We also note that existing techniques often require considerable time to be spent in data collection and analysis; for example, orbit response matrix analysis at the ATF takes several hours. If frequent tuning of the damping rings is required (as may be expected, given the sensitivity to magnet alignment at the level of a few microns), it will be necessary to develop a technique that can be applied quickly, or, ideally, continuously.

Achieving the objective of developing techniques for low-emittance tuning will involve the following tasks:

1. Evaluate sensitivity of present baseline and alternative lattice designs to a variety of magnet misalignments, and compare the results with the lattices of existing facilities. This will be an ongoing task as new lattice designs are developed.
2. Perform a rigorous comparison of existing low-emittance tuning techniques, to understand how the effectiveness of the various techniques depends on the lattice design, initial survey alignment, and functionality and performance of instrumentation.
3. Develop alternative low-emittance tuning techniques based on, for example, model independent analysis or phase advance analysis, and compare the effectiveness of these techniques with existing methods.

Potential Investigators on these tasks will be:

Richard Helms
Mark Palmer
Kosmas Panagiotidis
Gregg Penn
Ina Reichel
David Rubin
Marco Venturini

Andy Wolski
Mike Zisman

A total effort of 2 FTE per year for two years will be required. Work will include mostly simulation and theoretical studies, though tests of tuning strategies on operating facilities (e.g. ATF, ALS, APS, CEsrTA) would be valuable (see Objective 2.1.4.3).

No M&S budget is required.

Work on these tasks is ongoing. The goal is to complete all tasks by the end of 2008 as input for the Engineering Design Report (EDR).

The required input includes:

- Latest damping rings lattice designs; and lattices for existing storage rings to be used for benchmarking and tests.
- Data from previous studies of low-emittance tuning.
- Estimates of anticipated survey alignment precision and diagnostics performance (BPMs, beam size monitors etc.)

The main deliverables will be:

- Guidance on requirements for the damping rings lattice design to ease sensitivity to magnet alignment errors.
- Guidance on the requirements for survey, alignment and stabilization of magnets (Objective 2.1.4.2), and the configuration of the orbit and coupling correction scheme (specification and layout of the diagnostics, and orbit and coupling correction magnets – Objective 2.1.4.5).
- Optimized tuning methods that can be applied to demonstrate vertical emittance of less than 2 pm in existing facilities (Objective 2.1.4.3).

If the objective is not achieved, then achieving and maintaining the specified vertical emittance in the damping rings will be at risk. There could be significant impact on the luminosity of the ILC.

Objective 2.1.4.2: Specify requirements for survey, alignment and stabilization

High Priority

As described for Objective 2.1.4.1, achievement of the specified vertical emittance of 2 pm in the damping rings will depend on accurate survey and alignment of the magnets, particularly the quadrupoles and sextupoles. Current estimates suggest that the required accuracy will be demanding, particularly given two damping rings in a single tunnel. Developments with the lattice design, low emittance tuning techniques (Objective 2.1.4.1) and experimental experience (Objective 2.1.4.3) could all impact the required accuracy of the magnet alignment. It is important that careful studies of the alignment accuracy are carried out, taking account of developments in the lattice design, tuning techniques etc., so that the specifications remain realistic.

Achieving this objective will involve the following task:

1. Use the results of studies of low-emittance tuning techniques (taking account of lattice design developments, instrumentation specifications etc.) to

determine appropriate, realistic specifications on the alignment for the various magnets in the damping rings.

A total effort of 0.5 FTE per year over two years will be required.

No M&S budget is required.

The goal is to complete the task by 2008, to provide results for the Engineering Design Report.

The required input includes:

- Results from studies of low-emittance tuning techniques (Objective 2.1.4.1) showing the dependence of the final achieved vertical emittance on the initial alignment accuracy.
- Information from survey and alignment experts, for the implications (in time and cost) of specifications for different levels of alignment accuracy.

The deliverables will include:

- Guidance for work on lattice design, instrumentation and diagnostics, low-emittance tuning techniques etc., on whether further work is needed to ease requirements on initial alignment of the damping ring magnets.
- Specifications for the survey and alignment accuracy required for the damping ring magnets.

If this objective is not accomplished, there is a risk that the damping ring design will develop in such a way as to require alignment accuracy for the magnets that is unrealistic (not technically feasible), or can only be achieved at excessive cost.

Objective 2.1.4.3: Demonstrate < 2 pm vertical emittance

Very High Priority

Simulation studies leading to the development of low-emittance tuning techniques should take place as defined by Objective 2.1.4.1. However, experimental verification of any technique is essential for validation of any proposed technique. The performance of any low-emittance tuning technique will be sensitive to details of the machine configuration, performance of the instrumentation and diagnostics, and how the technique is implemented. While many important effects (e.g. systematic dependence of BPM readings on bunch charge, temperature, etc.) can be included in the simulations, real-world experience will be essential for providing realistic conditions for use in the simulations. More importantly, validation of any low-emittance tuning technique will ultimately rely on demonstration of its effectiveness in an operating machine; such a demonstration will also be necessary to validate the specifications associated with the technique, including the lattice design, configuration, functionality and performance of the instrumentation, diagnostics and correction elements, and accuracy of survey alignment of the magnets (Objective 2.1.4.2).

Achieving this Objective will require the following tasks:

1. Evaluation of the availability of facilities (for example, ATF, CesrTA, APS, ALS etc.), and their capability to meet the requirements of low-emittance tuning techniques.

2. Upgrade to diagnostics and instrumentation and orbit and coupling correction systems, where necessary.
3. Implementation of low-emittance tuning techniques, and evaluation of the results (and implications for the damping rings).

A total effort of 2 FTE per year for 2 years will be required.

An M&S budget of \$250k per year for 2 years will be needed at the ATF, for upgrades to instrumentation and diagnostics (mostly, the BPM electronics). Some additional M&S funds may be needed at other facilities.

The goal is to demonstrate 2 pm vertical emittance in an operating storage ring by the end of 2008.

This Objective requires access to appropriate facilities (e.g. ATF, CsrTA, APS, ALS). Results from development of low-emittance tuning techniques (Objective 2.1.4.1) are also required.

The deliverables will include:

- Demonstration that the vertical emittance goal of 2 pm in the damping rings is achievable.
- A range of essential information and data for improving the completeness of low-emittance tuning simulations, for optimising low-emittance tuning techniques (Objective 2.1.4.1), and for specifying design requirements for the lattice, coupling correction schemes (2.1.4.5), instrumentation and diagnostics performance, and survey and alignment accuracy (Objective 2.1.4.2).

If the Objective is not achieved, there will remain doubt as to whether the emittance goal of 2 pm in the damping rings is achievable.

Objective 2.1.4.4: Specify support schemes for damping rings magnets

High Priority

The stability requirements on the damping ring magnets are demanding; the magnet stands must be capable of supporting magnets in the upper and lower damping rings with the necessary stability. Vibrations (at tens or hundreds of hertz) and slow ground motion (over hours, days and weeks) are a concern. Magnets may be placed on individual stands, or grouped on girders; the support scheme that is used will affect the relative alignment accuracy that can be achieved between different magnets, and will have implications for orbit and coupling correction. Specifications are needed for magnet supports that will meet the stability requirements. Technical designs for support stands will be needed for the Engineering Design Report.

The following tasks must be completed:

1. Identify the different options for support schemes. Evaluate the impact of the different options on relative alignment accuracy, and low-emittance tuning.
2. Complete a detailed specification for a particular choice of support scheme for the baseline configuration.
3. Prepare technical designs for the magnet supports, which will allow evaluation of the achievable alignment accuracy, and modeling of the magnet vibration and long-term magnet alignment stability.

4. Construct prototype supports, and evaluate stability performance.

A total effort of 2 FTE per year for 2 years will be required.

An M&S budget of \$100k will be required for construction of the prototype supports.

Tasks 1-3 should be completed by 2008, to provide results for the Engineering Design Report. Task 4 can be completed following the EDR.

Results from simulations and experimental studies of low-emittance tuning, and from studies of required alignment accuracies (Objectives 2.1.4.1, 2.1.4.3 and 2.1.4.2) will be required as input for the above tasks.

The deliverables will include:

- Specification of baseline magnets support scheme, consistent with alignment and stability requirements (Objective 2.1.4.2) and low-emittance tuning techniques (Objectives 2.1.4.1 and 2.1.4.3).
- Models of magnet vibration and stability for input to studies of low-emittance tuning (Objective 2.1.4.1) and beam stability.
- Prototype magnet supports, ready for final engineering design.

If this Objective is not achieved, the support scheme and the designs of the supports themselves (critical components for achieving and maintaining low emittance and good stability) will remain incomplete before approval is sought for construction.

Objective 2.1.4.5: Specify orbit and coupling correction scheme

High Priority

Achieving and maintaining ultra-low emittance and good beam stability in the damping rings will depend on, amongst other things, the quantities, locations, functionality and performance of the instrumentation and diagnostics, and the orbit and coupling correction elements. The instrumentation and diagnostics that need to be considered in this context are principally the beam position monitors, and devices for measuring the beam size. The orbit and coupling correction elements will principally consist of steering magnets and skew quadrupoles.

Insufficient quantities, poor performance or inappropriate positioning of the instrumentation will make it difficult or impossible to achieve the specified ultra-low vertical emittance, with resulting adverse impact on the ILC luminosity. However, BPMs are expected to make a significant contribution to the machine impedance, which could affect beam stability; it is therefore undesirable to include more BPMs than necessary. Quantities of orbit and coupling correction elements are principally a question of cost; note that costs are incurred not just in the steering magnets and skew quadrupoles themselves, but also in their power supplies, cables, and in the control system.

An optimized scheme for orbit and coupling correction is necessary for the specifications on beam quality and stability to be achieved, without excessive cost or adverse impact on machine impedance. To achieve the Objective of defining an optimized scheme, the following tasks must be achieved:

1. Identify the options for coupling and correction schemes, including variable numbers and positions of monitors and correctors.

2. Evaluate the performance of the various schemes.
3. Specify the coupling and correction scheme for the baseline configuration, including quantities, functionality, performance and locations of the diagnostics and instrumentation, and the orbit and coupling correction elements.

A total effort of 1 FTE per year for 2 years will be required.

No M&S budget will be required.

All the above tasks should be carried on in parallel with developments in the lattice design, and with studies of low-emittance tuning (Objectives 2.1.4.1, 2.1.4.3) and studies of magnet alignment and stabilization (Objectives 2.1.4.2 and 2.1.4.4). The tasks should be completed by the end of 2008, to provide results for the Engineering Design Report.

The main deliverable will be a detailed description and specification for the orbit and coupling correction scheme to be used in the damping rings.

References

- [1] Y. Honda et al, "Achievement of Ultralow Emittance Beam in the Accelerator Test Facility Damping Ring," *Phys. Rev. Lett.* **92**, 054802-1 (2004).
- [2] C. Steier, D. Robin, A. Wolski, G. Portmann, J. Safranek, "Coupling Correction and Beam Dynamics at Ultralow Vertical Emittance in the ALS," *Proceedings of PAC 2003*, Portland, Oregon (2003).
- [3] K. Kubo, "Simulation Study of Low Emittance Tuning of the Accelerator Test Facility Damping Ring at KEK," *Phys. Rev. STAB* **6**, 092801 (2003).
- [4] J. Safranek et al, "Matlab-based LOCO," *Proceedings of EPAC 2002*, Paris, France (2002). A. Wolski, M.D. Woodley, J. Nelson, M.C. Ross, "Analysis of KEK-ATF Optics and Coupling Using LOCO," *Proceedings of EPAC 2004*, Lucerne, Switzerland (2004).
- [5] See, for example, Y. Cai, J. Irwin, M. Sullivan and Y.T. Yan, "Application of Model-Independent Analysis to PEP-II Rings," *Proceedings of PAC 2001*, Chicago, Illinois (2001).
- [6] D. Sagan, R. Meller, R. Littauer, D. Rubin, "Betatron Phase and Coupling Measurements at the Cornell Electron/Positron Storage Ring," *Phys. Rev. STAB* **3**, 092801 (2000).

Work Package 2.2.1
Impedance-Driven Single-Bunch Instabilities

Work Package Coordinator: Marco Venturini

Potential Investigators

ANL

Yong-Chul Chae

Cockcroft Institute

Roger Jones

Oleg Malyshev

Andy Wolski

IHEP

Jie Gao

(Yi-Peng Sun)

LBNL

Marco Venturini

SLAC

Karl Bane

Sam Heifets

Kwok Ko

Zenghai Li

Cho Ng

Gennady Stupakov

DRAFT

Summary of Required Resources

Objectives

S3 WBS	Objective	Priority
2.2.1.1	Development of single-bunch impedance models	High*
2.2.1.2	Characterization of single-bunch impedance-driven instabilities	Very High

*Results from Objective 2.2.1.1 are required input for Objective 2.2.1.2.

Staff Effort (FTE)

S3 WBS	2007	2008	2009	2010
2.2.1.1	3.0	3.0		
2.2.1.2	1.5	1.5		

M&S (US\$k)

S3 WBS	2007	2008	2009	2010
2.2.1.1	0	0		
2.2.1.2	0	0		

Facilities

No experimental facilities are required.

Objectives

Objective 2.2.1.1: Development of single-bunch impedance models

High Priority

Although not designated as very high priority, the activities contained in this Objective are instrumental and essential to the achievement of the very high priority Objective 2.2.1.2, as accurate characterization of single-bunch instabilities depends critically on accurate modeling of the machine impedance (or wake fields).

Ideally, the impedance model should be developed in concert with the technical designs for the actual components to be installed in the machine. If limitations in resources do not allow this, a lesser but still satisfactory goal is to demonstrate the acceptability of an impedance model based on the design of components from existing machines, appropriately scaled to meet the basic specifications for the damping rings. This will still provide useful information for the technical design of the damping ring components. Of course, modeling will be extended to the actual machine components if appropriately detailed designs for these become available within the time frame for the present study.

Characterization of the impedance will have to be mostly based on detailed and computationally-intensive numerical calculations starting from the design of realistic machine components, with focus on sources of short-range wake fields. However, simplified models of impedance based on analytical formulas will also be considered for intermediate assessment of the instability thresholds. For some impedance sources, such as the resistive wall or coherent synchrotron radiation in the dipoles and wigglers, modeling based on analytical formulas could be fully satisfactory.

Achieving the goals of this Objective will require the following tasks:

4. Compile a list of all relevant sources of short-range wake fields, and rank the list according to the expected significance of the contribution.
5. Construct or retrieve suitable designs for the relevant machine components. Scale available designs to meet the specifications for the damping rings.
6. Develop analytical models for those impedance sources that do not require detailed numerical description.
7. Develop simplified analytical models for the machine components in order to construct (tentative) preliminary estimates of the total machine impedance, while more detailed numerical models are being constructed.
8. Carry out numerical computations of the wake fields for the relevant machine components.

Potential Investigators on these tasks will be:

Karl Bane
Yong-Chul Chae
Jie Gao
Sam Heifets
Roger Jones
Kwok Ko
Oleg Malyshev
Cho Ng

Gennady Stupakov
Yi-Peng Sun
Marco Venturini
Andy Wolski

To complete all the tasks, including technical design work for the significant vacuum chamber components, will require 3 FTE per year for 2 years. Some additional effort would be useful to permit consideration of alternate designs for some of the machine components to be modelled. No M&S budget is required.

Work on the above tasks has already started and should be completed by the end of 2008.

The required input includes:

- Specifications for the lattice and vacuum chamber components; with detailed technical designs of the vacuum chamber components if possible.
- Designs of relevant machine components (these will be scaled from machines previously studied if the technical designs for the actual components in the damping rings are not available).

The deliverables will include:

- Detailed description of the total short-range wake fields for the damping rings, based on realistic modelling of machine components. This deliverable is required so that an estimate can be made of the current thresholds for single-bunch instabilities (Objective 2.2.1.2).
- Recommendations for optimization of parameters affecting beam stability (in conjunction with Objective 2.2.1.2).
- Feedback and guidance regarding the technical designs of the components in the vacuum chambers of the damping rings (in conjunction with Objective 2.2.1.2).

If the goals of this Objective are not achieved, it will not be possible to make an accurate estimate of the current threshold for single bunch instabilities. A partial achievement of the goals (e.g. if a limited number of machine components can be accurately modelled) could result in unreliable characterization of the instabilities.

The coordinator for this Objective will be Marco Venturini.

Objective 2.2.1.2: Characterization of single-bunch impedance-driven instabilities

Very High Priority

Single-bunch instabilities are particularly insidious as, unlike their multi-bunch counterparts, they cannot be corrected by existing feed-back systems. Careful effort should be devoted to ensuring that single-bunch instabilities can be avoided altogether by a proper design of the machine components and specification of lattice and beam parameters. It is then essential that accurate estimates of the instability thresholds are produced, and feedback regarding design modifications is provided before the technical designs of critical machine components are finalized. Evaluation of instability thresholds can be done using a variety of presently-available methods,

which invariably depend on an accurate characterization of all significant sources of short-range wake fields.

Achieving the goals of this Objective will involve the following tasks:

1. Acquire detailed and reliable models of the short-range wake potentials from all relevant machine sources (Objective 2.2.1.1).
2. Use the available models of short-range wake fields to estimate the instability thresholds (using, for example, time-domain simulations and linearized Vlasov equation analysis), and characterize the nature of the instability.
3. Identify the main sources of instability.
4. Determine modifications required (to the lattice design, and technical designs of components) to ensure a reasonable margin of safety between the nominal operating parameters and the instability thresholds.

Potential Investigators for these tasks are:

Karl Bane
Yong-Chul Chae
Jie Gao
Sam Heifets
Gennady Stupakov
Yi-Peng Sun
Marco Venturini

1.5 FTE of effort per year for two years will be required to complete the tasks required for this Objective. No M&S budget is required.

Some work on this task has already been carried out. In addition to the efforts that led to the preliminary estimates contained in [1], work has also been done in benchmarking the existing numerical tools for instability calculations [2]. Present and future activities will have to be conducted in close coordination with those underway in Objective 2.2.1.1. The investigators involved in this Objective should respond as soon as the wake field models for additional machine components become available, and maintain an updated estimate of the instability thresholds. This will allow for early detection of possible problems, and also guarantee a timely delivery of the final assessment of the instability thresholds by the end of 2008.

The required input includes:

- Impedance/wake field models developed in Objective 2.2.1.1.
- Lattice design and beam parameter specifications.

The deliverables will include:

- Estimates of the instability thresholds.
- Characterization of the beam dynamics associated with the instability.
- Feedback and guidance on the specifications and technical designs for the lattice and vacuum chamber components.

In the absence of a reliable estimate of single-bunch instability thresholds there is a risk that the damping rings may not be able to provide a stable beam at full intensity, with the result that the luminosity of the ILC could be seriously compromised.

Remedial measures could require the replacement of substantial sections of the vacuum chamber.

The coordinator for this Objective will be Marco Venturini.

References

- [1] A. Wolski, J. Gao, and S. Guiducci, LBNL-59449 (2006).
- [2] ILC Damping Rings R&D Workshop, Cornell University, Ithaca, NY, September 26-28 2006,
<https://wiki.lepp.cornell.edu/ilc/bin/view/Public/DampingRings/ILCDR06/>

DRAFT

Work Package 2.2.3 Electron Cloud

Work Package Coordinator: Mauro Pivi

Potential Investigators

CERN

Warner Bruns
Fritz Caspers
Daniel Schulte
Frank Zimmermann

Cockcroft Institute

Oleg Malyshev
Ron Reid
Andy Wolski

Cornell

Jim Crittenden
Mark Palmer

DESY

Rainer Wanzenberg

FNAL

Panagiotis Spentzouris

INFN-LNF

David Alesini
Roberto Cimino
Alberto Clozza
Pantaleo Raimondi
Cristina Vaccarezza

KEK

John Flanagan
Hitoshi Fukuma
Ken-ichi Kanazawa
Kazuhito Ohmi
Kyo Shibata
Yusuke Suetsugu

LANL

Bob Macek

LBNL

John Byrd
Christine Celata
Stefano de Santis
Art Molvik
Gregg Penn
Marco Venturini
Mike Zisman

PAL

Eun-San Kim

Rostock University

Aleksander Markovik
Gisela Poplau
Ursula van Rienen

SLAC

Karl Bane
Bob Kirby
Alexander Krasnykh
Brett Kuekan
Nadine Kurita
Cho Ng
Alexander Novokhatski
Mauro Pivi
Tor Raubenheimer
John Seeman
Lanfa Wang

Summary of Required Resources

Objectives

S3 WBS	Objective	Priority
2.2.3.1	Characterize electron-cloud build-up	Very High
2.2.3.2	Develop electron-cloud suppression techniques	Very High
2.2.3.3	Develop modelling tools for electron-cloud instabilities	Very High
2.2.3.4	Determine electron-cloud instability thresholds	Very High

Staff Effort (FTE; excludes operational support for Facilities)

S3 WBS	2007	2008	2009	2010
2.2.3.1	2.0	2.0		
2.2.3.2	3.0	3.0		
2.2.3.3	2.0	2.0		
2.2.3.4	1.5	1.5		

M&S (US\$k; excludes operating costs for Facilities)

S3 WBS	2007	2008	2009	2010
2.2.3.1	0	0		
2.2.3.2	730	920		
2.2.3.3	0	0		
2.2.3.4	0	0		

Facilities

CesrTA would provide a unique facility for studies of electron cloud in wigglers (Objective 2.2.3.1), and can also provide data on electron cloud under other conditions. Experimental data from several machines (CesrTA, PEP-II, KEKB, DAΦNE, LHC) will be needed for proper completion of all the Objectives.

Objectives

Objective 2.2.3.1: Characterize electron-cloud build-up

Very High Priority

Coupling between an electron cloud and the circulating beam can cause a single-bunch (head-tail) instability and incoherent tune spreads that may lead to increased emittance, beam blow-up and ultimately to beam losses directly affecting the collider luminosity. Many of the electron cloud effects have been evaluated by simulations.

There has been significant progress in characterizing the build-up in most areas of the damping rings, and the simulations have been benchmarked and are believed to be reliable. However, there are still uncertainties in the wiggler sections where the electron cloud could have a significant impact. Further studies are also needed of electron cloud trapping in quadrupoles.

Achieving the objective of characterizing the electron cloud build-up will involve the following tasks:

9. Perform experimental measurements of electron cloud build-up in wiggler sections in CsrTA, and benchmark simulation results against the data collected.
10. Continue effort to measure electron cloud in CsrTA, PEP-II, KEKB, DAΦNE and LHC, and benchmark codes against the data collected.
11. Perform measurements of electron cloud density by transmission of RF signals in PEP-II.
12. Perform simulations of electron cloud build up in the ILC damping rings with different fill pattern configurations as possible mitigation.
13. Compile the electron cloud density obtained by simulations over the machine lattice of the ILC damping rings.

Potential Investigators on these tasks will be:

Warner Bruns
John Byrd
Christine Celata
Jim Crittenden
Stefano De Santis
Mark Palmer
Mauro Pivi
Marco Venturini
Lanfa Wang
Frank Zimmermann

A total effort of 2 FTE per year for two years will be required. Work will include simulation and experimental studies.

No M&S budget is required.

Work on these tasks is ongoing. The goal is to complete all five tasks by the end of 2008 as input for the Engineering Design Report (EDR).

The required input includes:

- Experimental data from various machines, including CEsrTA, PEP-II, KEKB, LHC, and DAΦNE.
- Lattice design and initial specifications for vacuum system, wigglers and general magnets for the damping rings (including a variety of alternative design specifications).
- Beam parameters and possible fill patterns (bunch charge, bunch spacing) for the damping rings.

The main deliverable will be:

- Detailed and reliable description of electron cloud density in various sections (wiggler, bends, quadrupoles, field-free) of the positron damping ring, under a variety of possible conditions. The conditions will include ranges of beam parameters, and specifications for the vacuum system, and for the wiggler and other magnets.

The detailed description of the electron cloud density is required as input for studies of electron cloud instability (Objectives 2.2.3.3 and 2.2.3.4); to support design work on the vacuum system (Objectives 3.1.1.1 and 3.1.1.2); and to guide the selection of possible fill patterns for the damping rings.

If the objective is not achieved, there will remain considerable uncertainty regarding the impact of electron cloud on the ability of the positron damping ring to deliver the specified beam quality and stability. There is a potentially significant impact on ILC luminosity. Remedial measures following commissioning could be difficult and expensive.

Objective 2.2.3.2: Develop electron-cloud suppression techniques

Very High Priority

Actions to suppress the electron cloud are required for the positron damping ring. The B-factories have implemented external solenoid fields to mitigate electron cloud in field-free regions, which constitute a large fraction of the PEP-II and KEKB positron rings [1, 2]. Notably, the electron cloud effect in KEKB remains a major obstacle to shorter bunch spacing and higher luminosity, even with solenoid windings [3]. In the ILC damping rings, beam instability can occur even if electron cloud is present only in the wigglers and dipoles, where external solenoid fields are not effective in preventing build-up of the cloud. Therefore, R&D is required into techniques that can be applied in regions of strong magnetic fields to prevent build-up of electron cloud.

Preliminary studies (mostly based on simulations, but supported by some laboratory measurements) suggest that techniques such as grooves in the wall of the vacuum chamber, or the use of clearing electrodes, could be effective at suppressing the electron cloud in regions of strong wiggler or dipole fields [4, 5]. On the basis of these studies, a single 6 km positron damping ring has now been adopted in the baseline configuration for the ILC. However, a demonstration of the effectiveness of possible suppression techniques is required to validate this choice; an (expensive) alternative is to use two positron damping rings to reduce the beam current. Any technique used to mitigate build-up of electron cloud must be consistent with stringent requirements for large aperture and low impedance in the damping rings.

Achieving the objective of developing suppression techniques for the electron cloud will involve the following tasks:

5. Test clearing electrode concepts by installing chambers with clearing electrodes in existing machines and in magnetic field regions in CesrTA, PEP-II, KEKB, LHC and HCX (LBNL). Characterize the impedance seen by the beam, the generation of higher order modes (HOMs), and the power deposited in the electrodes.
6. Test “groove” concepts by installing chambers with grooved or finned surfaces in existing machines, including bend and wiggler sections in CesrTA and PEP-II. Characterize the impedance and HOMs.
7. Study coating techniques, test the conditioning of coated surfaces and characterize their performance *in situ* in CesrTA, PEP-II and KEKB.

Potential Investigators on these tasks will be:

David Alesini
Fritz Caspers
V. Ivanov (?)
Alexander Krasnykh
Bob Macek
Art Molvik
Cho Ng
Mark Palmer
Mauro Pivi
Yusuke Suetsugu
Lanfa Wang

A total effort of 3 FTE per year for two years will be required. Work includes mainly experimental studies with support of simulations.

An M&S budget of \$730k in 2007, and \$920k in 2008 is required.

Work on these tasks should start now. The goal is to complete all three tasks by the end of 2008 as input for the Engineering Design Report (EDR).

The required input includes:

- Experimental data from machines including CesrTA, PEP-II, KEKB, LHC. Data should include detailed comparison of electron cloud density with beam in sections with mitigation techniques implemented (grooved and/or coated surfaces, clearing electrodes, etc.) compared with the electron cloud density in sections without mitigating techniques.

The deliverables will include:

- Technical specifications for techniques to be used to suppress build-up of electron cloud in the positron damping ring, consistent with aperture and impedance requirements.
- Guidance for the design of the vacuum chamber material and geometry (Objective 3.1.1.1), and for the technical designs for principal vacuum chamber components (Objective 3.1.1.2).

If electron cloud mitigation techniques are not developed and demonstrated to be sufficiently effective for the proposed baseline positron 6 km ring, then two 6 km

rings or a single ring of much larger circumference are possible alternatives. If the electron cloud density is not reduced below the threshold level for beam instabilities, then the positron damping ring will be unable to provide a beam meeting the specifications for quality, stability and intensity; this will have a potentially significant impact on the luminosity of the ILC.

Objective 2.2.3.3: Develop modeling tools for electron-cloud instabilities

Very High Priority

Simulation codes [6] have been useful for characterizing the single-bunch instability driven by electron cloud in proposed storage ring designs. However, there is a need for more extensive benchmarking against experimental data. Also, differences in the results from different codes need to be understood and resolved. Finally, the simulation codes need to be applied to the damping rings to determine the impact of electron cloud on beam stability, given the results of the studies of cloud build-up under various conditions (Objective 2.2.3.1).

Because of the long computing time required to model accurately the complex interaction between the beam and the electron cloud, simulation codes typically “lump” the interaction at a finite number of “interaction points” (IPs) around the ring. The number of IPs is limited by the available computer power. Benchmarking of simulation codes shows that better agreement between different codes can be achieved by increasing the number of IPs, but differences are still an order of magnitude.

Although qualitative comparisons between simulation codes and experimental observations (for example, of the effects of chromaticity, or the signals present in the tune spectra) are leading to increased confidence in the results of the simulation codes, further benchmarking is needed to refine the models before the results can be considered sufficiently reliable that a machine design can be based upon them.

Achieving the objective of developing modeling tools for electron-cloud instabilities will involve the following tasks:

1. Implement existing quasi-static simulation codes, and demonstrate agreement for existing designs for the damping rings.
2. Develop 3D simulation codes that include accurate models of wiggler fields.
3. Develop combined build-up and instability codes into a single, self-consistent modeling tool.
4. Track the beam in a lattice with a distributed electron cloud at each ring element.

Potential Investigators on these tasks will be:

Kazuhito Ohmi
Frank Zimmermann
Panagiotis Spentzouris
Christine Celata
Eun-San Kim
Mauro Pivi

A total effort of 2 FTE per year for two years will be required. Work involves mostly simulations.

No M&S budget is required.

Work on these tasks is ongoing. The goal is to complete all four tasks by the end of 2008 as input for the Engineering Design Report (EDR).

The required input includes:

- Experimental data from machines including CEsrTA, PEP-II, KEKB, and LHC.

The deliverables will include:

- Support for the determination of electron-cloud instability thresholds (Objective 2.2.3.4) for the positron damping ring.
- Guidance for the specification of the secondary electron yield as input for the characterization of an electron-cloud build-up (Objective 2.2.3.1).

If modeling tools for electron-cloud instabilities are not successfully developed, the risk is to underestimate the effect and make more likely to be hampered by difficulties in generating the specified emittance in the 6 km damping ring. On the opposite side, a possible risk would be to overestimate the instability threshold and consequently apply solutions that raise the ring impedance and increase costs. Finally, if electron cloud suppression techniques are found to be effective (Objective 2.2.3.2) the developing of modeling tools for electron-cloud instabilities (this Objective 2.2.3.3) and determining electron-cloud instability thresholds (Objective 2.2.3.4) would decrease in priority.

Objective 2.2.3.4: Determine electron-cloud instability thresholds

Very High Priority

Simulations for the baseline 6 km damping ring lattice indicate a threshold for single-bunch instability at an averaged cloud density of around 1.4×10^{11} electrons/m³, but there is still considerable uncertainty in the results. The instability appears as an incoherent emittance growth [7, 8], which would limit the beam quality in the damping rings at full intensity, and adversely impact the luminosity. If mitigation techniques are not used and electron cloud is allowed to develop, the threshold density is reached after few bunch passes. A more accurate determination of the electron-cloud instability thresholds is important when considering what level of mitigation is needed. Furthermore, there is a need to compare the actual simulation results for the ILC damping ring with different codes [9].

Achieving the objective of determining the electron-cloud instability thresholds will involve the following tasks:

1. Resolve discrepancies in predictions for the ILC damping ring from different codes.
2. Benchmark the simulation codes against experimental data from existing machines.

3. Perform simulations which include various magnetic field configurations (field-free regions, dipoles, quadrupoles) and a range of realistic electron cloud distributions (from Objective 2.2.3.1).
4. Perform 3D simulations including wiggler sections.
5. Perform self-consistent build-up and instability simulations.
6. Obtain detailed and reliable characterization of single-bunch electron cloud instability for the positron damping ring.

Investigators on these tasks will be:

Kazuhito Ohmi
Frank Zimmermann
Panagiotis Spentzouris
Christine Celata
Eun-San Kim
Mauro Pivi

A total effort of 1.5 FTE per year for two years will be required. Work involves mainly simulations, with support of experimental data.

No M&S budget is required.

Work on these tasks is undergoing. The goal is to complete all tasks by the end of 2008 as input for the Engineering Design Report.

The required input includes:

- Experimental data from machines including CesrTA, PEP-II, KEKB, and LHC.

The deliverables will include:

- Prediction of the electron cloud driven single-bunch instability threshold for the positron damping ring.
- Specification of the maximum permissible cloud density in the positron damping ring, as a target for the development of mitigation techniques (Objective 2.2.3.2).

Knowledge of the electron-cloud instability thresholds is essential when considering what level of mitigation of the electron cloud will be required. If instability occurs at a density that is lower than predicted, the mitigation techniques may be insufficient to ensure the required beam quality. Conversely, if it is thought necessary to reduce the cloud density to a much lower level than absolutely required, there is a risk that the mitigation techniques selected will raise the ring impedance and increase costs.

References

- [1] H. Fukuma in *Proceedings of ELOUD04*, Napa, California (2004) and CERN-2005-001.
- [2] A. Kulikov, A. Novokhatski and J. Seeman in the *Proceedings of ELOUD04*, Napa (2004) and CERN-2005-001.
- [3] KEKB 2005 Annual Report, p.2,
<http://www-kekb.kek.jp:16080/pukiwiki/index.php?Documents>

- [4] L. Wang, G. Stupakov, T. Raubenheimer, in *Proceedings of EPAC06*, Edinburgh (2006).
- [5] L. Wang, H. Fukuma, S. Kurokawa, M. Pivi, and G. Xia, in *Proceedings of EPAC06*, Edinburgh (2006).
- [6] F. Ruggiero, F. Zimmermann, Simulation Codes Web Repository http://care-hhh.web.cern.ch/care-hhh/simulation_codes_catalogue_and_repository.htm
- [7] A. Wolski, J. Gao, and S. Guiducci, LBNL-59449 (2006).
- [8] M. Pivi, T. O. Raubenheimer, L. Wang, K. Ohmi, R. Wanzenberg, A. Wolski, Frank Zimmermann, in *Proceedings of EPAC06*, Edinburgh (2006) and submitted for publication in *Phys. Rev. ST AB*.
- [9] K. Ohmi, in *Proceedings of ELOUD04*, Napa, California, (2004).

DRAFT

Work Package 2.2.4 Ion Effects

Work Package Coordinators: Mauro Pivi and Marco Venturini

Potential Investigators

CERN

Warner Bruns
Daniel Schulte
Frank Zimmermann

Cornell

Jim Crittenden
Mark Palmer

DESY

Eckhard Elsen
Guoxing Xia

KEK

Takashi Naito
Nobuhiro Terenuma
Junji Urakawa

LBNL

John Byrd
Christine Celata
Stefano de Santis
Marco Venturini

SLAC

Mauro Pivi
Lanfa Wang

DRAFT

Summary of Required Resources

Objectives

S3 WBS	Objective	Priority
2.2.4.1	Characterize ion effects	Very High
2.2.3.2	Specify techniques for suppressing ion effects	Very High

Staff Effort (FTE; excludes operational support for Facilities)

S3 WBS	2007	2008	2009	2010
2.2.4.1 and 2.2.4.1	6.0	4.0	4.0	

M&S (US\$k; excludes operating costs for Facilities)

S3 WBS	2007	2008	2009	2010
2.2.4.1 and 2.2.4.2	200?	200?		

Facilities

Experimental data from several machines (including CEsrTA, KEK-ATF) will be needed for proper completion of all the Objectives.

Objectives

Objective 2.2.4.1: Characterize ion effects

Very High Priority

and Objective 2.2.4.2: Specify techniques for suppressing ion effects

Very High Priority

This Work Package consists of two Objectives, the first to “Characterize Ion Effects” (Objective 2.2.4.1) and the second to “Specify Techniques for Suppressing Ion Effects” (Objective 2.2.4.2). Both of these objectives are ranked as “Very High Priority”. The two objectives are considered together in the description of this Work Package.

Ion effects have long been recognized as possible sources of current limitation in storage rings for negatively charged particles. Limitations in machines operating under normal conditions have so far been the result of “conventional” effects, in which ions are trapped in the potential well of the circulating beam over multiple turns. Effective cures have been developed and include beam-shaking, electrodes, and use of clearing gaps between bunch trains.

More recently it was discovered that even if conventional ion trapping was suppressed, a “fast ion instability” (FII) [1] could develop under the more extreme machine parameters in damping rings for future linear colliders. Important parameters include the bunch size and beam current. Ions can be created during the passage of a single long bunch train, and cause emittance degradation before being cleared by a gap in the fill pattern. Simulations indicate that this effect is potentially very serious for the ILC electron damping ring. Fortunately, these simulations also suggest that splitting the bunch train into a number of shorter trains will be a viable solution for suppression of the fast ion instability. There is a pressing need to demonstrate that, by proper design for the machine, the instability growth rates can be brought within reach of feasible feedback systems.

While the qualitative aspect of the simulation results is not in question, there are still doubts about their accuracy. Fast ion instabilities have been detected in existing machines during experiments carried out under rather unconventional conditions, but these experiments have mostly provided proof of the existence of the effect, rather than a reliable benchmark of existing theory. For this reason, a significant portion of the required effort will be concerned with the design of experiments suited to accurate validation of present simulation models and computational tools. Further refinement of present simulation models may also be needed.

The ultimate goal is to ensure that the design (including specification of feedback system, vacuum levels, and bunch train patterns) is such that the damping rings will be capable of delivering a beam with the required quality.

Achieving the Objectives will involve the following tasks:

1. Validate existing theoretical models and simulation tools for the fast ion instability by carrying out suitable measurements in available storage rings.
2. Refine existing simulation tools beyond their current state or develop new tools if necessary to achieve acceptable agreement with the experiments.

3. Demonstrate the existence of viable machine designs capable of meeting the specifications for beam quality and stability, and show experimental feasibility of these designs using existing machines if possible.
4. Explore the effectiveness of a variety of mitigation techniques (such as clearing electrodes), if necessary.

Work on the above tasks will build on the experience accrued during the investigations for the baseline configuration choice [2] and subsequent studies. Potential Investigators on these tasks will be:

Warner Bruns
John Byrd
Christine Celata
Jim Crittenden
Stefano de Santis
Eckhard Elsen
Takashi Naito
Mark Palmer
Mauro Pivi
Daniel Schulte
Nobuhiro Terenuma
Junji Urakawa
Marco Venturini
Lanfa Wang
Guoxing Xia
Frank Zimmermann

An effort of 4 FTE in 2007, followed by 2 FTE per year in 2008 and 2009, will be required for experimental studies. Simulation and modelling work will require a further 2 FTE per year for 2007, 2008 and 2009.

An M&S budget of roughly \$200k per year will be needed to support the experimental studies.

Access to key facilities, including CesrTA and KEK-ATF will be required.

The required input includes:

- Designs for the lattice and for the vacuum system, and specifications for the feedback system.

The main deliverables will be:

- Experimental validation of theoretical models and simulation tools for the fast ion instability.
- Indication of machine design parameters (including bunch filling patterns, lattice optics, feedback and vacuum specifications) capable of delivering a beam with the required quality and stability without limitations from ion effects.
- Guidance for optimization of design of vacuum and feedback systems, and optimization of the optics design, to avoid limitations from ion effects.

If the Objectives are not met, the ability to deliver the required beam specifications at extraction could be compromised, resulting in reduced luminosity.

References

- [1] T. Raubenheimer and F. Zimmerman, Phys. Rev. E, 52, 5487 (1995).
- [2] A. Wolski, J. Gao, and S. Guiducci, LBNL-59449 (2006).

DRAFT

Work Package 3.5.1 Fast Injection/Extraction Kickers

Work Package Coordinator: Thomas Mattison

Potential Investigators

Cornell

Gerry Dugan
Robert Meller
Mark Palmer
David Rubin

FID-GmbH

Vladimir Efanov

FNAL

Marc Ross

KEK

Takashi Natio
Junji Urakawa

LBNL

Stefano de Santis

LLNL

Craig Brooksby
Ed Cook

LNF

David Alesini
Fabio Marcellini

SLAC

Craig Burkhart
Richard Cassel
Anatoly Krasnykh
Ray Larsen

UBC

Tom Mattison

UIUC

George Gollin

Summary of Required Resources

Objectives

S3 WBS	Objective	Priority
3.5.1.1	Develop a fast high-power pulser for injection/extraction kickers	Very High
3.5.1.2	Develop physics designs for kicker striplines	High

Staff Effort (FTE; excludes operational support for Facilities)

S3 WBS	2007	2008	2009	2010
3.5.1.1	6.0?	6.0?	6.0?	
3.5.1.2	2.0?	2.0?	2.0?	

M&S (US\$k; excludes operating costs for Facilities)

S3 WBS	2007	2008	2009	2010
3.5.1.1	800	800?	800?	
3.5.1.2	200	200?	200?	

Facilities

Experimental studies at the ATF have played a vital role in the recent development of kicker technology for the ILC damping rings; work at the ATF will continue to be of great importance as the focus of activities shifts to ATF2 (for studies of issues related to the beam delivery system). Other facilities, such as DAΦNE, and the A0 beamline at FNAL, will also play an important role in development of fast kicker technology.

Objectives

Objective 3.5.1.1: Develop a fast high-power pulser for injection/extraction kickers

Very High Priority

The extraction kicker must extract single bunches from the train without disturbing other bunches yet to be extracted, and the injection kicker must inject single bunches into the train without disturbing bunches yet to be extracted. Ideally, the sum of the electrical pulse width, stripline electrical propagation time, and stripline beam propagation time, should be less than twice the bunch spacing. This allows operation with no extra gaps in the bunch train or kicker rise or fall. For 6 ns bunch spacing, and 3 MHz kicker burst rate, performance close to this has been demonstrated with 30 cm striplines and FID GmbH pulsers. For alternative parameters with 3 ns bunch spacing and 6 MHz burst rate, there is not yet a demonstration of a satisfactory pulser. Even with 6 ns bunch spacing, there are concerns about the baseline noise between pulses, and the cost and single-source issues with FID GmbH pulsers.

The worst-case consequence of failing to develop an adequate damping ring kicker pulser is a damping ring that cannot function. More realistically, it might be necessary to increase the bunch spacing beyond 6 ns in the damping rings, presumably with proportionate reduction in luminosity. The 3 ns bunch spacing parameters imply that some effect has limited the feasible bunch charge, and it is desired to increase the number of bunches to compensate the loss of luminosity. If the kicker pulsers cannot support 3 ns bunch spacing, that luminosity loss would not be compensated, although operation with low bunch charge and increased bunch spacing would still be possible.

The R&D tasks involved ideally include:

1. Bench test fast pulser driving a resistive load to verify parameters (rise and fall times, amplitude, jitter, burst mode).
2. Bench test fast pulser driving mismatched loads (open, short) to verify robustness.
3. Bench test fast pulser driving stripline structures instrumented for kick field measurements, including cables and loads.
4. Beam test fast pulser and stripline unit with instrumentation to allow precision measurements of beam deflection as a function of the timing separation between bunch passage and kicker pulse.
5. Beam test fast pulser and stripline unit with sufficient circulating current to detect any adverse effect of beam-image currents on the pulser.
6. Perform long-term (operation over many months) reliability and stability tests.
7. Perform cost-engineering study.

As is appropriate for such a critical issue, there are several complementary pulser R&D efforts. Because pulser R&D work to date has been funded largely by laboratory initiative rather than GDE direction, the program has some overlaps and gaps. Improved coordination mechanisms are being put in place.

FID GmbH Pulsers

One thrust of effort is to use commercial pulsers from FID GmbH, and this has produced the best results to date. This small company makes a variety of very fast pulsers and is willing to develop customized systems. Many (although not all) of their devices use Fast Ionization Dynister (FID) switches. FIDs can switch far higher power levels than FETs, but have a maximum rep rate lower than the desired burst rate, so burst mode requires multiple devices and a non-trivial power-combiner. Their devices also typically have a Delayed Step Recovery Diode (DSRD) circuit as the final stage. A consequence of this appears to be that the “off” state of the pulser can have undesirable large currents (of order 1% of the peak current), extending for hundreds of nanoseconds before and after the pulse. Whether this can be controlled, or whether the machine can tolerate it, is an important issue.

Pulsers from FID have been purchased or borrowed for testing with beam at the A0 line at Fermilab (Cornell, UIUC), ATF at KEK, and in the near future with DAΦNE at LNF. While these programs address some of the above tasks, they are either (useful) demonstrations rather than real development, or are part of another laboratory program that happens to have relevance to ILC.

A proposal has been made by FID GmbH to develop a next-generation pulser capable of higher voltage and higher burst rate. A partner institution should be found to pursue this, and negotiate the technical goals, and a funding model for the cost of several hundred thousand dollars should be developed.

Inductive Adder FET Pulsers

- *SLAC-LLNL effort*
- *Substantial funding*
- *Aimed at beam testing at ATF*
- *Aimed at high-availability*
- *Need to aim for faster rise/fall to be relevant*
- *Is this possible? May need radical geometry changes*

Delayed Step Recovery Diode Pulsers

- *SLAC-SBIR effort independent of FID GmbH*
- *Modest funding, smart people*
- *Addresses baseline issues, and single-source issues*

Other Pulser Technologies

- *Intend to start working with saturating ferrite pulse-sharpeners / baseline-filters*
- *Will probably use Behlke FET switches (why have Behlke switches dropped off the radar, anyway?)*

Objective 3.5.1.2: Develop physics designs for kicker striplines

High Priority

To be completed.

DRAFT