Mount stabilization for Shintake monitor-5

ATF2 meeting in Annecy October 15, 2007

Tatsuya KUME, Yosuke HONDA, and Toshiaki TAUCHI High Energy Accelerator Research Organization (KEK)

Taikan SUEHARA, YODA, OOROKU, YAMANAKA and KAMIYA The univ. of Tokyo

New optical table for Shintake monitor

-tentative design (view from down stream)



•Using optical table $(1.6 \times 1.7 \times 0.25 \text{ m})$

•Made of non-magnetic SUS honeycomb core

Specifications expected for new table support

- ~10nm of amplitude for incoherent vibration with floor
- \pm 5mm of adjustable range for height with accuracy of \pm 1mm
- \pm 2.5mm of adjustable range for horizontal perpendicular to beam with accuracy of \pm 1mm
- Not use magnetic material within 300mmφ around beam

Rigid mount for optical table

-side view outline





Work position in shield

-view from up stream



6/9

Positions to be set

-for preventing interference with shield construction



Plan

- Consider & design interferometer optics (Univ. of Tokyo & KEK)
 - Consider interferometer optics optimized for ATF2.
 - Decide table size and mounting holes for new optical table.
 - Show size and mounting holes to manufacturer (Herz co.) by end of Oct.
- Make new optical table and mount (~Feb.,2008., Herz co.)
- Put new table and mount on tentative place @ ATF2 (on ~Feb.-Mar., 2008., Herz co.)
- Replace them on work place (=IP) (Mar.-May, 2008, U of Tokyo & KEK)
- Align and fix new table on IP (~May, 2008. (U of Tokyo & KEK)
- Vibration measurement and analysis (May, 2008., Herz co.)

Schedule

	2007			2008					
	Oct.	Nov.	Dec.	Jan.	Feb.	Mar.	Apr.	May	Jul.
Overall	Design	Make			Optics install & test (Tentative place @ATF2)			Install	
Univ. of Tokyo & KEK	Design new optical ☆ Design fixing			table	Install Optics				
					Optics te		cs test	→ ☆ Install	
	Design table mount			t					
HERZ Co. LTD.	Make new optical table & table mount				☆ Put on ntative place @ATF2		√ Vibration measurement @IP		