

# Benchmarking for Lol

Tim Barklow & Andrei Nomerotski

SiD AC, 8 Oct 2007

# From Physics Studies to Benchmarking

- Entering a new phase: Lol in 2008 and EDR in 2010
- Emphasis of physics studies will shift from ILC Physics Case towards
  - Evaluation and comparison of detector choices
  - Realities required by engineering (ex material)
  - Realities required by reconstruction algorithms
- New Research Director will define a set of processes common to different concepts but also will allow concepts to choose processes highlighting their strong features
  - WWS will reinstitute a working group to suggest processes

# Considerations

- Requirements to processes
  - Highlight physics case for ILC
  - Be generic so more physics scenarios are covered → signature oriented
  - Be sensitive to detector parameters
- What's different from previous studies: matured tools
  - real geometries
  - material effects
  - effects from realistic reconstruction algorithms in Tracker and Calorimeters
- Reality may decrease sensitivity to physics – need to think about improved analysis techniques to recover
- Lol is a strong time constraint and will help to streamline this activity
  - The list reduced after Snowmass 2005 from 27 processes to 8

# Benchmarking processes

reduced list from Snowmass 2005 report hep-ex/0603010

0. Single  $e^\pm, \mu^\pm, \pi^\pm, \pi^0, K^\pm, K_S^0, \gamma, 0 < |\cos\theta| < 1, 0 < p < 500$  GeV
1.  $e^+e^- \rightarrow f\bar{f}, f = e, \tau, u, s, c, b$  at  $\sqrt{s}=0.091, 0.35, 0.5$  and 1.0 TeV;
2.  $e^+e^- \rightarrow Z^0h^0 \rightarrow \ell^+\ell^- X, M_h = 120$  GeV at  $\sqrt{s}=0.35$  TeV;
3.  $e^+e^- \rightarrow Z^0h^0, h^0 \rightarrow c\bar{c}, \tau^+\tau^-, WW^*, M_h = 120$  GeV at  $\sqrt{s}=0.35$  TeV;
4.  $e^+e^- \rightarrow Z^0h^0h^0, M_h = 120$  GeV at  $\sqrt{s}=0.5$  TeV;
5.  $e^+e^- \rightarrow \tilde{e}_R^+\tilde{e}_R^-$  at Point 1 at  $\sqrt{s}=0.5$  TeV;
6.  $e^+e^- \rightarrow \tilde{\tau}_1^+\tilde{\tau}_1^-$ , at Point 3 at  $\sqrt{s}=0.5$  TeV;
7.  $e^+e^- \rightarrow \tilde{\chi}_1^+\tilde{\chi}_1^-/\tilde{\chi}_2^0\tilde{\chi}_2^0$  at Point 5 at  $\sqrt{s}=0.5$  TeV;

# Comments on Processes

- Reduced list is a good starting point and likely to be used by RD
- We need to decide which other processes we want to consider
- Benchmarking group will discuss this with all subsystems
  - Subsystems may have more than one hardware option. We should try to be positive about it - look for processes emphasizing strong sides of different options.
- We need to be realistic what we can be done in a year
- SiD needs to engage RD & WWS in discussion re benchmarking processes

# Benchmarking Vertexing

1.  $e^+e^- \rightarrow f\bar{f}$ ,  $f = e, \tau, u, s, c, b$
3.  $e^+e^- \rightarrow Z^0h^0$ ,  $h^0 \rightarrow c\bar{c}, \tau^+\tau^-, WW^*$ ,  $M_h = 120$  GeV at  $\sqrt{s}=0.35$  TeV;
4.  $e^+e^- \rightarrow Z^0h^0h^0$ ,  $M_h = 120$  GeV at  $\sqrt{s}=0.5$  TeV;
6.  $e^+e^- \rightarrow \tilde{\tau}_1^+\tilde{\tau}_1^-$ , at Point 3 at  $\sqrt{s}=0.5$  TeV;

- Main criteria: Highly efficient  $b\&c$  – tagging

- Other possible processes

- Charm tagging in dominant  $b$  background

$$ee \rightarrow H^0 A^0 \rightarrow b\bar{b}b\bar{b}$$
$$ee \rightarrow \tilde{t}_1\tilde{t}_1$$

- Taus: 3-prong vertexing for collimated decays, impact parameter to tag 1-prong decays

# Benchmarking Tracking

0. Single  $e^\pm, \mu^\pm, \pi^\pm, \pi^0, K^\pm, K_S^0, \gamma, 0 < |\cos\theta| < 1, 0 < p < 500$  GeV
1.  $e^+e^- \rightarrow f\bar{f}, f = e, \tau, u, s, c, b$  at  $\sqrt{s}=0.091, 0.35, 0.5$  and 1.0 TeV;
2.  $e^+e^- \rightarrow Z^0 h^0 \rightarrow \ell^+\ell^- X, M_h = 120$  GeV at  $\sqrt{s}=0.35$  TeV;
5.  $e^+e^- \rightarrow \tilde{e}_R^+ \tilde{e}_R^-$  at Point 1 at  $\sqrt{s}=0.5$  TeV;

- Main issues

- **ALGORITHMS**

- Momentum resolution/Pattern recognition

- V0 reconstruction

- Forward tracking

- Other processes

- Busy multi-jet events

- Reconstruction of  $E_{cm} : ee \rightarrow \mu\mu$

# Benchmarking Calorimetry

0. Single  $e^\pm, \mu^\pm, \pi^\pm, \pi^0, K^\pm, K_S^0, \gamma, 0 < |\cos\theta| < 1, 0 < p < 500$  GeV
3.  $e^+e^- \rightarrow Z^0h^0, h^0 \rightarrow c\bar{c}, \tau^+\tau^-, WW^*, M_h = 120$  GeV at  $\sqrt{s}=0.35$  TeV;
4.  $e^+e^- \rightarrow Z^0h^0h^0, M_h = 120$  GeV at  $\sqrt{s}=0.5$  TeV;
7.  $e^+e^- \rightarrow \tilde{\chi}_1^+\tilde{\chi}_1^-/\tilde{\chi}_2^0\tilde{\chi}_2^0$  at Point 5 at  $\sqrt{s}=0.5$  TeV;

- **Issues**

- Energy resolution, di-jet mass resolution with and without beam energy constraint
- **Algorithms** are probably even more important than in tracking
- Compensating CAL?

- **Other processes**

- $ee \rightarrow WW\nu\nu$
- $\pi^0$  reconstruction: tau polarization, b-tagging



# Benchmarking Others

- Muons

- purity: punchthroughs, decays in flight

0. Single  $e^\pm, \mu^\pm, \pi^\pm, \pi^0, K^\pm, K_S^0, \gamma, 0 < |\cos\theta| < 1, 0 < p < 500$  GeV

2.  $e^+e^- \rightarrow Z^0h^0 \rightarrow \ell^+\ell^-X, M_h = 120$  GeV at  $\sqrt{s}=0.35$  TeV;

- Forward systems

- Luminosity

- Electron veto (two-photon bkg)

6.  $e^+e^- \rightarrow \tilde{\tau}_1^+\tilde{\tau}_1^-$ , at Point 3 at  $\sqrt{s}=0.5$  TeV;

- Anything else ?

# Strategy of Benchmarking

- SiD is a concept with distinct features
  - compact detector with precise silicon tracking and compact calorimeters inside the magnet which allows for fine segmentation at acceptable cost
- Optimization should be done within these constraints
  - As opposed to a wide open optimization
  - Different from ILD which needs to decide how to average LDC & GLD
- Select a point in detector parameter space and check for an optimum around this point
  - Need to decide how to select the point and how to define the range of parameters

# Tools for Benchmarking

- Most of results so far used Fast Monte Carlo
- Full detector simulation (SLIC) and reconstruction code are available and there are already results that used the full simulation chain
- Important to use uniform tools – org.lcsim, JAS3, WIRED4
- Need a simulation chain which would work out of the box
- Need strong support from simulation group

# Random Thoughts

- Decide on Lol plots early so work can be focussed on what's needed for Lol
- Manpower issues – identify people for key processes
- Clearly the optimization will be much affected by cost factors. Need to disentangle this?
- Suggest common samples for all concepts

# Status and Plans

- Resumed benchmarking meetings
  - First meeting tomorrow 9 Oct
  - Will invite subsystems to discuss benchmarking
- Learning SiD software...
- Timeline
  - Oct 2008 submit Lol
  - June 2008 Benchmarking studies ready
  - Feb 2008 All key analyses on-going
  - Dec 2008 First sample analysis
  - Oct 2008 Tools ready