

# Status of RPC based DHCAL

*H. Weerts, Argonne Nat. Lab.*

*for*

*DHCAL RPC group*




**Argonne**  
NATIONAL  
LABORATORY

*... for a brighter future*

Run 208:0 Event 158

Time: 6838157

Hits: 30 Energy: xxx mips



**CALICE**  
Calorimeter for ILC



U.S. Department  
of Energy

UChicago ►  
Argonne<sub>LLC</sub>

A U.S. Department of Energy laboratory  
managed by UChicago Argonne, LLC

TILC09, Tsukuba, Japan, April 2009

# Outline

Vertical Slice Test-- Intro

RPC characteristics

Performance

- Rate capability

- Positron showers

- Pion data

- Environmental dependence

Future

Conclusions

# Vertical Slice Test

## Test of whole system with

Up to 10 RPCs, each  $20 \times 20 \text{ cm}^2$   
(Up to 2560 channels)

## RPCs


Up to 9 two-glass designs

1 one-glass design


Only use RPC0 - RPC5 in analysis of  $e^+$ ,  $\pi^+$

Only use RPC0 - RPC3 for rate dependence

## Two-glass design



## One-glass ('exotic') design



# Vertical Slice Test

## Test of whole system with

Up to 10 RPCs, each 20 x 20 cm<sup>2</sup>  
(Up to 2560 channels)

## RPCs

Up to 9 two-glass designs  
1 one-glass design  
Only use RPC0 – RPC5 in analysis of  $e^+$ ,  $\pi^+$   
Only use RPC0 – RPC3 for rate dependence

## Absorber

For cosmic rays, muon, pions, electrons: Steel (16 mm) + Copper (4 mm)

Rate capability measurement (120 GeV protons): 16 mm PVC with whole cut out in center

## Test beam

Collected data in Fermilab's MT6 beam line




## Cosmic Rays

Collected data for ~18 months


Slice of a  
“complete”  
system



# RPC performance








Operation:  
 HV: 6.0-6.3KV  
 Threshold: 110  
 Effic. ~90%



# RPC performance

Operation:  
 HV: 6.0-6.3KV  
 Threshold: 110  
 Effic: 90-95%






Fits theoretically motivated

91 Hz/cm<sup>2</sup>


346 Hz/cm<sup>2</sup>

588 Hz/cm<sup>2</sup>

1795 Hz/cm<sup>2</sup>



# Rate Capability




$\Delta t$  between two protons


Time between consecutive events

# Two chambers: position of hit in 2<sup>nd</sup> chamber

1800Hz/cm<sup>2</sup>





# Simulation Strategy and comparison to test beam data



With muons – tune  $a$ ,  $T$ , ( $d_{\text{cut}}$ ), and  $Q_0$   
With positrons – tune  $d_{\text{cut}}$   
Pions – no additional tuning

Monte Carlo simulations



Broadband  $\mu$



Positron Showers



2 GeV  $e^+$

8 GeV  $e^+$



# Positron Showers

Monte Carlo simulations - 6 layers  
Monte Carlo simulations - Infinite stack



# Response to Pions

Simulation needs to be redone with tuned parameters...

## Data at

1, 2, 4, 8, 16 GeV (electrons rejected by Čerenkov)

**6 layer stack corresponding to  $0.7 \lambda_1$**


## Analysis separates

- Non-interacting pions/muons
- Pions interacting in first layers
- Pions interacting later (rejected)

Exactly one cluster in first layer  
 Distance  $R < 5$   
 Number of hits in **first** layer  $< 5$

### MIP selection

Number of hits in **second** layer  $< 5$




### Plot total #hits

Nice MIP peaks

Gaussian distributions

### Pion selection





Number of hits in **second** layer  $\geq 5$



# Response to Pions

## MIP selection

Mean and sigma ~independent of beam momentum  
 Mean not very well reproduced by simulation  
 → Beam contains muons, simulation does not  
 (data are cleaner !!!)  
 Width of distributions adequately reproduced





## Pion selection



Measurements at 16, 8 and 4 GeV/c  
 Not sufficient statistics at 2, 1 GeV/c  
 Non-linearity due to leakage  
 Adequate agreement with simulation

# Environmental

Noise Rate(Uncorrected Data)



Efficiency (Uncorrected Data)





Data collected over period of 18 months

Weather station added about 9 months ago


- Barometric pressure
- Ambient temperature
- Air humidity




Multiplicity (Uncorrected Data)




Noise Rate Vs.  $\Delta T(-22.5^\circ\text{C})@100\text{kpa}$




Efficiency Vs.  $\Delta T(-22.5^\circ\text{C})@100\text{kpa}$




Multiplicity Vs.  $\Delta T(-22.5^\circ\text{C})@100\text{kpa}$




Noise Rate Vs.  $\Delta P(-97.3\text{kpa})@22.5^\circ\text{C}$



Efficiency Vs.  $\Delta P(-97.3\text{kpa})@22.5^\circ\text{C}$



Multiplicity Vs.  $\Delta P(-97.3\text{kpa})@22.5^\circ\text{C}$




Assume linear dependence on p,T,H


$$F_i(p,T,H) = F_{i,0} + b_{i,1} \Delta p + b_{i,2} \Delta T + b_{i,3} \Delta H \quad \text{with } i = N,E,M$$

Apply correction  $\rightarrow$  check RMS of distributions


RMS Comparison (Noise Rate)



RMS Comparison (Efficiency)




RMS Comparison (Multiplicity)




Bonus: performance versus gas flow rate


Noise Rate Vs. Gas Flow Rate



Efficiency Vs. Gas Flow Rate



Multiplicity Vs. Gas Flow Rate



## Description

40 layers each  $\sim 1 \times 1 \text{ m}^2$

Each layer with 3 RPCs, each  $32 \times 96 \text{ cm}^2$

Readout of  $1 \times 1 \text{ cm}^2$  pads with one threshold (1-bit)

$\sim 400,000$  readout channels

Layers to be inserted into the existing AHCAL CALICE structure

## Purpose

Validate DHCAL concept

Gain experience running large RPC system

Measure contained hadronic showers in great detail

Validate hadronic shower models

## Status

Started construction in fall 2008

### DCAL III chip

Produced in 2008

Received 11 wafers with 966 chips each → 10626 chips

→ Packaged chips by early March--done

Testing to be done

'by hand' at Argonne for first chips (in progress)

by robot at FNAL (being programmed)

### Pad- and Front-end board

On critical path

32 x 48 cm<sup>2</sup> → 4 x 6 chips

Being designed (first prototype in hand)

### Data concentrator

Design and firmware completed

To be implemented onto front-end board

Item	Status	Outstanding problems/tasks	Critical path
RPC construction	Several prototypes exist	Test of thin-glass 2-glass chambers Test of full-scale 1-glass chambers (requires final front-end board) Develop production procedure	No
DCAL chips	In hand	Robot testing	Until ~May
Front-end boards	Being prototyped	Final design/prototype (ASIC in hand) Testing procedure being developed	~May - October
Back-end	Being produced	Small modifications to existing design	No
Gas system	Being assembled	None	No
HV system	Completed	None	No
DAQ software	Being modified	None	No
OFFLINE software	Being developed	None	No

# Conclusions

Learned a lot from vertical slice test and extended operation of chamber stack

Excellent foundation for next step

Building planes/electronics/DAQ for 1m<sup>3</sup> test calorimeter to go into CALICE stack