Muon Purity and Detection Efficiency Variation With Depth in an SiD Type Detector C. Milstene- Fermilab- ILC Workshop-Vancouver-July19-24-2006

Work done in collaboration with G. Fisk and A. Para (Fermilab)

The Detector

(Not quite SiD)

ECal	HCal	Coil	Mudet	
(30Layer)	(34Layer)		(15Layer)	
X0 - 21.75	X0 - 39.44	X0 - 13	X0 - 79.5	
Λ - 0.872	Λ - 4.08	Λ - 2	Λ - 8.4	
dE/dx - 190MeV	dE/dx - 800MeV	dE/dx - 362MeV	dE/dx - 1400MeV	
Segmentation: ΔΦ =Δθ= 3.7 mr	Segmentation: ΔΦ =Δθ= 5.23 mr		Segmentation: ΔΦ =Δθ= 21 mr	

Mu Detector:

240cm thick for the magnet flux return:

10 cm Fe plates

15 instrumented gaps.

The Detector Display



The Data

10000 bbar-b jets events generated with Geant4

- P>3GeV required in order for the Muon to reach the Muon Detector
- A polar angle cut define the barrel.

The Algorithm

Rely on the 2 main characteristic properties of the muon

- 1. The muon creates a repetitive pattern of 1 to 2 hits per cell all the way
- 2. The muon travels deep without interacting whereas hadrons are filtered out
- Each Charged track with a good fit in the tracker hits are
- Collected in a road in $(\Delta \Phi, \Delta \theta)$ in ECal, HCal and Mudet
- -Accounting for v&B and dE/dx effects
- -requiring no more than 2 hits/cell
- -requiring a given depth reached into the Muon detector

Layers with Non-zero Hits in HCal and Mudet



Filter to Hadrons-The Cuts

Hadrons tend to interact \rightarrow Irregular hit patterns They don't reach out

1/ we cut on large energy deposit in the path

- 2/ we cut on void on 2-3 consecutive layers
- 3/ we require at least 1 hits on the last 4 layers of HCal and less than 4 hits/layer (still allows neutral from neighbor tracks)

Layers with > 3 Hits (Typical of Hadron activity) In HCal & Mudet



A b Interacting Hadron Content



Purity versus Efficiency



The Purity improves from 69% end of HCal (4.95λ) to 94% end of Mudet(15 λ)

The Efficiency improves from 95% to 99.6%

<u>Remark</u>: Muons which do not enter the layer e.g. bending into the endcaps at a certain level of their path, are not included in the normalization.

HCal & MuDet Barrel - Purity and Efficiency Cuts

Conditions for 10,000 b-b_bar	Muons	Pions	K's	Protons
Tracker Recons & Final Tracks	739	18024	4303	1712
Good Fit Tracker	715	17120	4072	1579
1 or 2 hits in each of the last 5 layers of Hcal. (No 0's)	700	357	204	15
MuDet ≥12hits,≥12layers	671	77	50	5
Min Mudet Hits ≤2 Max Mudet Hits≤7	670	69	39	5

Momentum distributions in b jets

In bbar-b jets events the muon is ~1.7% of the particle population

	π	k	proton	μ
Total Gen	55805	8310	2816	1147
Gen > 3GeV	18666	4473	1622	787
Fract. >3GeV	34%	54%	58%	69%
Recon>3GeV	18024	4303	1614	739
Good Fit	17120	4072	1579	717
Identified	69	39	5	670
As µ				
Rejection Efficiency	1/261	1/104	1/322	93.5%

Study of Muons @ The End of their Trajectory

- A muon detector allows to filter out hadrons and allows to detect the muons in b jets,(1.7% of the jet particle population) with 93.5% efficiency
- The code is developed further to detect the muons curling back at the end of their trajectory.
 We use a momentum dependant dE/dx, with the Bethe-Block formula (in progress).
- The dE/dx @ reconstruction is also compared to the dE/dx @simulation with Geant4

Reconstructed And Simulated -Details



Reconstructed-Yellow C. Milsténe Simulated- Green and blue

Event Reconstructed Before and Now

Before

Now



C. Milsténe

Comparison dE/dx G4-Sternheimer on Iron



Conclusion

- A study of Muon ID and Purity in the detector shows that in bbar-b jets one is able to identify the muons (1.7% of the population) with an efficiency which can reach 99.6% and a purity of 95%
- We have also shown that we get a steady improvement of purity and muon efficiency with depth. The purity rises from 69% at the end of HCal to 94% at the end of Mudet and the efficiency from 95% to 99.6%

It requires just the instrumentation of part of the return iron of the magnet.

- The code is being developed to take a better care of the muons at the end of their trajectory.
- Due to small losses of barrel muons to the endcap the muon efficiency will improve further with the inclusion of the endcap to the code in development.

Last Layer With Activity



C. Milsténe

The upper figure shows the layer number where the muon reaches zmax. All the muons that reach zmax in layer 11 or higher meet the μ ID requirement. I.e. they are detected. The plot shows that most of the barrel muons above 3 GeV/c stay in the barrel and meet the muon penetration requirement for μ ID.

The lower figure is a blow-up of the upper histogram that shows the exit layer for those muons that do not meet the penetration requirement of 12 or more layers. 33 barrel muons exit the barrel before they reach z-max, so they are un-detected muons; they do not penetrate \geq 12 layers. 18

This document was created with Win2PDF available at http://www.daneprairie.com. The unregistered version of Win2PDF is for evaluation or non-commercial use only.