


LHC Beam Operations Past, Present and Future

K. Foraz – CERN (Acknowledgement : R. Bailey)







Operation envelope

Progress with beam in 2009 2010-2011





LHC nominal performance

Nominal settings									
Beam energy (TeV)	7.0								
Number of particles per bunch	1.15 10 ¹¹								
Number of bunches per beam	2808								
Crossing angle (μrad)	285								
Norm transverse emittance (µm rad)	3.75								
Bunch length (cm)	7.55								
Beta function at IP 1, 2, 5, 8 (m)	0.55,10,0.55,10								

Derived parameters									
Luminosity in IP 1 & 5 (cm ⁻² s ⁻¹)	10 ³⁴								
Luminosity in IP 2 & 8 (cm ⁻² s ⁻¹)*	~5 10 ³²								
Transverse beam size at IP 1 & 5 (μm)	16.7								
Transverse beam size at IP 2 & 8 (μm)	70.9								
Stored energy per beam (MJ)	362								

^{*} Luminosity in IP 2 and 8 optimized as needed








Instantaneous luminosity

$$L = \frac{N^2 k_b f}{4\pi\sigma_x \sigma_y} F = \frac{N^2 k_b f \gamma}{4\pi\varepsilon_n \beta^*} F$$


"Thus, to achieve high luminosity, **all one has to do** is make (lots of) high population bunches of low emittance to collide at high frequency at locations where the beam optics provides as low values of the amplitude functions as possible." PDG 2005, chapter 25

- Nearly all the parameters are variable (and not independent)
 - Number of particles per bunch
 - Number of bunches per beam
 - Relativistic factor (E/m_o)
 - Normalized emittance
 - Beta function at the IP
 - Crossing angle factor
 - Full crossing angle
 - Bunch length
 - Transverse beam size at the IP






LHC performance drivers






Energy: Evolution of target





Energy: the way back




2010-2011



Intensity: limits 2010 2011

- Collimation system conceived as a <u>staged system</u>
 - First stage to allow 40% of nominal intensity at 7 TeV
- Imperfections bring this down
- Machine stability and reproducibility also play a role
- Cleaning gets easier at lower energies



Fix I_{max} to 6 10¹³ protons per beam at 3.5TeV (about 20% nominal intensity)

30MJ stored beam energy



Higher intensities

- With experience assume that we can
 - Move to tight settings
 - Achieve 0.1% loss rates


- Then need to install something more
 - Proposal exists for next phase of collimation



β* and F: 2010 2011

- Lower energy means bigger beams
- $\varepsilon_n = \varepsilon \gamma \mid \sigma$

- Less aperture margin
- Higher β*
- > 150 bunches requires crossing angle
 - Requires more aperture
 - Higher β*
- Targets for 3.5TeV
 - 2 m no crossing angle
 - 3m with crossing angle




Operation with β^* between 1 m and 4 m very promising



β*: Evolution


- As energy increases, lower β* gets easier
- The squeeze is always going to be challenging
 - Optics
 - Collimator
- With experience, should be easier, but still ...



3/26/2010



LHC performance drivers at start






Early beam operation

2009			2010	2011				
Repair of Sector 34	1.18 r TeV	nQPS 6kA	3.5 TeV I _{safe} < I < 0.2 I _{nom} β* > 2 m	lons		3.5 TeV ~ 0.2 I _{nom} β* ~ 2 m	Ions	
No Beam	В		Beam			Beam		

- Energy limited to 3.5 TeV by the stabilizers
- 2010
 - Intensity carefully increased to collimation limit
 - $-\beta^*$ pushed as low as possible
- 2011
 - Run at established limits








Operation envelope
Progress with beam in 2009
2010-2011



15

Targets with beam 2009



Technical Stop

Beam commissioning

SPS et al physics

AIMS

450 GeV collisions 10⁶ events

Ramp to 1.18 TeV
Collisions at 1.18 TeV

Do this with SAFE BEAMS

10¹² at 450 GeV \rightarrow 2 10¹¹ at 1.18 TeV

LIMITS

2 on 2 with 5 10¹⁰ per bunch at 1.18 TeV 4 on 4 with 2 10¹⁰ per bunch at 1.18 TeV




Milestones reached

Date	Day	Achieved
Nov 20	1	Each beam circulating. Key beam instrumentation working.
Nov 23	4	First collisions at 450 GeV. First ramp (reached 560 GeV).
Nov 26	7	Magnetic cycling established (reproducibility).
Nov 27	8	Energy matching done.
Nov 29	10	Ramp to 1.18 TeV.
Nov 30	11	Experiment solenoids on.
Dec 04	15	Aperture measurement campaign finished. LHCb and ALICE dipoles on.
Dec 05	16	Machine protection (Injection, Beam dump, Collimators) ready for safe operation with pilots.
Dec 06	17	First collisions with STABLE BEAMS, 4 on 4 pilots at 450 GeV, rates around 1Hz.
Dec 08	19	Ramp colliding bunches to 1.18 TeV
Dec 11	22	Collisions with STABLE BEAMS, 4 on 4 at 450 GeV, > 10 ¹⁰ per bunch, rates around 10Hz.
Dec 13	24	Ramp 2 bunches per beam to 1.18 TeV. Collisions for 90mins.
Dec 14	25	Collisions with STABLE BEAMS, 16 on 16 at 450 GeV, $> 10^{10}$ per bunch, rates around 50Hz.
Dec 16	27	Ramp 4 on 4 to 1.18 TeV. Squeeze to 7 m. Collisions.





Injection







Beam dump













Collimation after beam based set up (Ralph)






Aperture scans – IR5 H shown






Beta-beat comparison 450 GeV and 1.18 TeV





Production!





Data recorded


<u>"stage"</u>	<u>Total hours</u>
4x4 5e9 p/bch	16 hrs
4x4 1.5e10 p/bch	26 hrs
16x16 1e10 p/bch	1.5 hrs
	43.5 hrs


Estimated numbers of pp interactions recorded by experiments


		able beams ors partly on)	Stable beams (full detector on)		
	450GeV	1.18 TeV	450 GeV		
ALICE	40k	33k	~ 400k		
ATLAS	~ 320k	~ 34k	~ 540k		
CMS	~ 100k	~18k	~ 410k		
LHCB		~ 40k	~ 250k		





Experiments events














Summary of progress with beam 2009

- Excellent machine availability
- Excellent performance of all accelerator systems
- Huge amount achieved in 4 weeks
- All targets met and more
- All done with safe beams
- Minimum changes made in the interest of expediency
- Plenty to think about
- Great collaboration between machine and experiments








Operation envelope
Progress with beam in 2009
2010-2011






5/2/2010 V1.4


2010 plan



450 GeV phase 1 / Ramp to 3.5 TeV 450 GeV phase II / Ramp to 3.5 TeV Collide / Squeeze / Collide Colliding, safe, stable, squeezed beams



Increase intensity in steps x2
Week of running after each step
No crossing angle
43 on 43 at 2m



Increase stored energy in steps of 2MJ Week of running after each step Bunch trains and crossing angle 10³² cm⁻² s⁻¹

					Beam tup		Start Ion Physics						
		Oct				Nov				Dec			
Wĸ	39	40	41	42	43	44	45	46	47	48	49	50	51
Мo	27	4	- 11	(*	25	,		15	22	29	Б	13	20
Tμ					1		9						
We				8	(-						
Ты					}		IOI						
Fr					((approx 4	weeks)					Xmas Day
S.)								
Su				0	1		N Company						

Ions (early scheme, 62 bunches per beam)
Same magnetic machine as for protons
2 weeks to switch
4 weeks ion run



°az - CFRN 27



2010 strategy


- In 2009
 - We corrected Q Q' coupling orbit
 - Otherwise optics were frozen
 - Reference orbit established
 - Protection devices set up and fixed

- In 2010
 - We correct everything we can with safe beams
 - Then establish references
 - Then set up protection devices
 - Any further change will require another iteration



2010 progress with safe beams

- Some difficulties to get new QPS operational
- 450 GeV work completed to date
 - Q Q' coupling orbit measured and corrected
 - Optics (beta-beating) measured and corrected
 - Established references
 - Collimation set up
 - Injection and associated protection
 - Extraction and associated protection
 - RF
- Ramp to 3.5 TeV done last week
 - Optics
 - Collimation set-up...
- Target for first colliding stable 3.5 TeV beams March 30th





Rates in 2011

Energy	TeV	3.50	3.50	3.50	3.50	3.50	3.50	3.50	3.50
Month		Mar	Apr	May	Jun	Jul	Aug	Sep	Oct
Bunch intensity	1.E+10	7	9	9	9	9	9	9	9
Bunches / beam		432	432	560	720	720	720	720	720
Emittance	μm	3.75	3.75	3.75	3.75	3.75	3.75	3.75	3.75
β*	m	2	2	2	2	2	2	2	2
Luminosity 1 & 5	cm-2 s-1	9.2E+31	1.5E+32	2.0E+32	2.5E+32	2.5E+32	2.5E+32	2.5E+32	2.5E+32
Protons		3.0E+13	3.9E+13	5.0E+13	6.5E+13	6.5E+13	6.5E+13	6.5E+13	6.5E+13
% nominal		9.4	12.0	15.6	20.1	20.1	20.1	20.1	20.1
Current	mA	54.4	70.0	90.7	116.6	116.6	116.6	116.6	116.6
Stored energy	MJ	16.9	21.8	28.2	36.3	36.3	36.3	36.3	36.3
Beam size 1 & 5	um	44.8	44.8	44.8	44.8	44.8	44.8	44.8	44.8
Initial luminosity	cm-2s-1	9.17E+31	1.52E+32	1.97E+32	2.53E+32	2.53E+32	2.53E+32	2.53E+32	2.53E+32
Integrated/month	pb-1	52.37	86.58	112.23	144.30	144.30	144.30	144.30	144.30
Integrated	pb-1	52.37	138.95	251.18	395.48	539.78	684.07	828.37	972.66



Summary

- LHC is up and running with beam in 2009
 - Excellent performance with safe beams
- In 2010 & 2011
 - Limited in energy due to interconnects Fixed in 2012
 - Limited in intensity by collim. cleaning syst..... Solution proposed
 - Limited in β^* because of lower energies target 2m
- "Prudent step-by-step approach.... LHC is not a turnkey machine...."
 R. Heuer
- "We can take satisfaction in what we have achieved to date, while reminding ourselves, that we are breaking new ground technologically as well as scientifically". R. Heuer