Opening the Endcaps at the IP(?)

Karsten Buesser





ILD Workshop
Paris
28.01.2010

Opening on the Beam (- or not)?



- Present design foresees opening of the detector on the beam:
 - Partially split endcap yoke allows ~1m wide access space between coil and endcap calorimeters
 - Allows for limited maintenance in the beam position(?)
 - Every major work would be done in the parking position - push pull!
- But:
 - A real engineering challenge which puts hard boundary conditions on many other things





Tools for Access



CMS Experience: it is not trivial to access a 1m wide space several meters above the floor (beam height is at 9m).




➤ Small size cradle elevator (used for small interventions) :

Needed place between endcap and barrel: 1.6 m

The overall size on floor of engine is 1.3 m

➤ Crane truck (allowing heavier operation up to ≈full height) :

1.5 m on floor, 2 m needed for motion








QD0 Support



- Movable yoke endcap makes QD0 support complicated
- QD0 supported by pillar outside of the detector and suspended on tie rods from the cryostat
- Monitored by MONALISA, placed on actuators for alignment
- Vibration issues are under study
- Alternative QD0 support ideas are under study



MONALISA Integration





- MONALISA requires vacuum pipes for laser beams attached to QD0
- Need to be disconnected remotely controlled when the endcap is opened
- Needs a lot of engineering work

Case of Monalisa:

Final Doublet Stability and in-detector Interferometry

- •4 entries on one side,
- •2 on the other side,
- Lines going under the detector





- •It is an interferometric metrology system for continuous monitoring of position critical accelerator components
- •Consists of a fixed network of evacuated interferometric distance meters with nanometre type resolutions over O(10m)


See David Urner's talk at LCSW08

More CMS Experience



- Endcap deformations are in the order of 15mm
 - Will be better at ILD
- Ground deformations during movements can reach 5mm at a scale of 2m.
- Time for closing of the endcap is in the order of 1.5 days (sic!)
 - Has not been done very often so far. Learning-curve effect is visible.
- Moving 3000t pieces in a delicate environment (beam pipe is 1mm) is

(beam pipe is 1mm) is not trivial and needs throrough engineering



To Open or Not to Open (on the beam)



- From the engineering point of view it would be much simpler to do maintenance on the detector only in the parking position
 - Push-pull will bring the detector to the parking position in one day
- Question to all of us:
 - What do we really gain if we design the detector for the opening of the end-cap on the beam?
- Keep in mind:
 - Access space is VERY limited
 - Only limited access to TPC endplate, barrel and endcap calorimeters
 - No access to inner detector (VTX, SIT, FTD, etc.)
 - CMS experience: opening time for the endcaps could be in the order of one day.
 - "When people are moving heavy pieces in these conditions (...), they become extra careful as any accident has dramatic implications." (A. Hervé)
 - Engineering resources are EXTREMELY rare in ILD. If we spend many on the endcap we might miss them somewhere else
- Questions to be answered:
 - What maintenance could be done on your subdetector during this limited access?
 - How much luminosity would we loose if we wait with the maintenance until we pull out?
 - What is the lumi-loss risk with the more complicated opening scenario?

The Far Side....



- The art of engineering design seems sometimes to be miraculous to the outsider
- What looks like a good idea at some time might prove to be superfluous later
- Sometimes you need to know the history behind the visible....



To open or not?



- Comments reveived so far:
 - "Keep it simple, we can get more sophisticated when the machine has been approved."
 - "Think about the potential problems now so that they will not hit us later"
 - "Do not mix maintenance procedures with push-pull issues. Maintenance is ILD-internal, while push-pull involves the other detector as well."

- What do you need?
- Biggest problem: how do we decide on this or other topics?