

The ILD DBD

Frank Simon

MPI for Physics & Excellence Cluster ‘Universe’
Munich, Germany

LCWS 2012, Arlington, TX, USA, October 2012



Max-Planck-Institut für Physik
(Werner-Heisenberg-Institut)



TUM

LMU
Excellence Cluster
Universe

Outline


- The ILD Concept
 - Overview
 - Subsystems
- The ILD Detector System
- Software & Performance
- Summary

From the LOI to the DBD



The ILD Concept


ILD - Overall Design



ILD Design - General Considerations & Challenges

- Performance goals set by physics
 - Jet energy resolution < 3% - 4% over full relevant energy range
 - Track momentum resolution $\delta(1/p_T) \simeq 2 \times 10^{-5} / \text{GeV}/c$
 - Excellent vertexing for b & c identification
- Resulting main requirements and challenges
 - Highly granular PFA calorimeters
 - Low material budget in front of calorimeter
 - Power-pulsing, low power consumption
 - Triggerless readout
 - Highly integrated electronics


The Vertex Detector



- VTX design:
 - 3 (almost) cylindrical layers pairs from 16 mm to 60 mm
 - Alternative: 5 single layers, from 15 mm to 60 mm
 - Several technologies under study: CMOS Pixel Sensors, Fine Pixel CCDs, DEPFET, use of multiple technologies an option
 - Time stamping depends on technology
- Performance goal:
$$\sigma_b < 5 \oplus 10/p\beta \sin^{3/2} \theta \text{ } \mu\text{m}$$
- Requirements:
 - Spatial resolution < 3 μm close to IP
 - Material budget < 0.15% X_0 per layer
 - ▶ low power consumption!
 - Pixel occupancy not exceeding a few %


Vertex Detector Technologies

- Active development of several technologies, synergies with LHC & others
 - All provide low material budget by thin sensitive layers
 - Trade-off between readout speed and pixel size (no time stamping)
- CMOS pixel sensors
 - $\sim 17\mu\text{m}$ pixel precision layers, $17 \times 85 \mu\text{m}^2$ pixel fast layers to reduce effective occupancy
 - Low material double layer “PLUME” demonstrated
- FinePitch CCDs
 - $\sim 5 \mu\text{m}$ pixels in inner layers, $\sim 10 \mu\text{m}$ pixels further out
 - Small prototype successfully tested, (almost) full size prototype available
- DEPFETs
 - $\sim 20 \mu\text{m}$ pixels, all-silicon modules with integrated support structure






The Main Tracker: TPC

- Main tracker philosophy:
Continuous tracking for excellent pattern recognition and dE/dx capability instead of best possible single point resolution
- The ILD TPC
 - Up to 224 space-points per track
 - Single point resolution $< 100 \mu\text{m}$ in $r\phi$
 - Two-hit separation $\sim 2 \text{ mm}$ in $r\phi$
 - Low material budget: 5% X_0 in barrel region, $<\sim 25\%$ X_0 in the endcaps
 - Standalone momentum resolution $\delta(1/p_T) \simeq 10^{-4}/\text{GeV}/c$




Two main readout options:
GEMs, Micromegas
Alternative: pixel detectors

TPC Development




- Large prototype with “space frame” endplate
- Test in magnetic field up to 4 T
- Two readout technologies already tested:
Triple-GEM, Micromegas



extrapolated resolution < 100 μm
also beyond 2000 mm!

The Silicon Trackers




- Silicon tracking to complement the TPC main tracker:
 - Improved resolution
 - Time-stamping
 - Calibration of distortions & alignment
 - Extended coverage in the forward region
- Combined tracker resolution:
$$\delta(1/p_T) \simeq 2 \times 10^{-5} / \text{GeV}/c$$


- Inner tracking barrel SIT - 2 fake double-sided strip layers, 2 space points
 - Outer tracking barrel SET - 1 fake double sided strip layer, 1 space point
 - Outer forward tracking layer ETD - 1 fake double sided strip layer, 1 space point
 - Inner forward tracker FTD - 7 disks (2 pixel, 5 strip)
- Common technology & design for all strip sensors in the silicon trackers

Silicon Tracker Technology

- Philosophy: Compact, simple and cost-effective modules
 - ▶ Edgeless sensors and integrated pitch adapters developed in synergy with LHC upgrades




Only 50μm from end of strip to end of sensor!!!




integrated pitch adapter
in a second metal layer

Interferometric monitoring of FTD with fiber-optic sensors:
Monitor changes of environmental parameters, vibrations, ...



The Main Calorimeters



- Main calorimeters optimized for particle flow:
 - High granularity
 - Small Molière radius in ECAL for good particle separation & photon identification
 - Sufficient depth of the HCAL to limit leakage also at 1 TeV
 - Compact design to fit inside magnet
- ECAL with tungsten absorbers and silicon and/or scintillator readout
- HCAL with steel absorbers
 - Analog - Scintillator tiles with SiPMs
 - Semi-digital - Glass RPCs with 2 bit readout, Micromegas as alternative


Calorimeter R&D

- Calorimeter technology for ECAL & HCAL developed by CALICE:

Combined test-beam experiments
to demonstrate PFA calorimetry

One highlight:
Shower separation with PandoraPFA
in the SiW-ECAL and AHCAL physics
prototypes

- ▶ Good agreement with simulations
demonstrates realism of our full
detector simulations & physics studies




- Readout ASICs for all calorimeter types with a common basis
- Common DAQ system, data format:




The SiW ECAL

- PIN silicon pad readout with $5.5 \times 5.5 \text{ mm}^2$ pads




6.8 mm per double layer




Complete tungsten structure for technological prototype exists


Well-established technology: physics prototype in various beam times since 2006



The Scintillator ECAL



- Scintillator strips ($5 \times 45 \times 1 \text{ mm}^3$) read out with SiPMs
 - 6.9 mm per double layer, 0.1 mm more than SiW ECAL
 - Electronics based on AHCAL design - synergies!



Extensive tests with a physics prototype, first module of technological demonstrator now in test beam at DESY



- Recover $5 \times 5 \text{ mm}^2$ granularity with strip-splitting algorithm
- SiPMs / MPPC with higher smaller pixels under study to increase dynamic range
- Hybrid solutions together with Si layers (interleaved or as two sections) possible

Updated resolution plot?

-> Currently under review in CALICE


The Analog HCAL

- Based on $3 \times 3 \times 0.3 \text{ cm}^3$ scintillator tiles with embedded SiPM




Compact design: < 6 mm non-absorber material per layer

Well-established technology: Extensive tests in beam with a 8 000 channel system since 2006



Hadronic energy resolution
of physics prototype with
software compensation:
 $45\%/\sqrt{E} \oplus 1.8\%$


The Analog HCAL




First units (144 channels) of technological demonstrator currently in test beam: - embedded electronics, power pulsing, online zero suppression channel-by-channel auto-trigger, time stamping

embedded SiPM

technology: Extensive tests in beam
channel system since 2006






Shower in one Spiroc




The Semi-Digital HCAL

- Glass RPCs with 1 cm² pads
 - 3 thresholds per channel: allows to keep linearity to higher energies, improved resolution at high energies compared to purely digital mode

Full 1 m³ technological prototype with 430k channels & power-pulsing successfully tested in beam




Forward Calorimeters




- Luminosity measurement at the 10^{-3} level with LumiCal
- Bunch-by-bunch luminosity monitoring and fast feedback for beam steering with BeamCal
- Extended coverage to low polar angles
- ▶ The only subsystems with substantial radiation hardness requirements!

Silicon sensors for LumiCal - tested in beam




GaAs sensors and CVD Diamond for BeamCal




CVD Diamond shows excellent radiation hardness
GaAs shows a reduction of the charge collection efficiency to 20% after 7 MGy, still sufficient for MIP detection

Muon System, Yoke and Coil




- Instrumented iron yoke: Muon tracking and tail-catching
- ~ 10 mm thick, ~ 30 mm wide up to 2.7 m long extruded scintillator strips with SiPM readout

Default operations
at 3.5 T, magnet
designed for 4 T to
allow flexibility at
higher energy




The ILD Detector System

ILD Mechanical Design




- 5 Yoke rings
 - Mounted on air cushions for easy moving during assembly / dis-assembly / maintenance
- Central ring carries cryostat and solenoid:
 - Supports calorimeters, TPC and outer Si trackers
 - Inner detector & beam pipe supported from TPC

ILD Integration




- Assembly strategy with dedicated installation fixtures



- Service paths inside of the detector for power, data, cooling

The Experimental Hall




- Size of cryostat defines minimum diameter of access tunnel required for installation
 - For vertical access: Assembly of yoke rings and central detector system within cryostat on surface: 18 m diameter required
 - For horizontal access: Assembly of yoke rings and other large components in detector hall: > 8.7 m diameter required

ILD Software & Performance

ILD Simulation & Reconstruction


- Significant enhancements compared to the LOI
 - Increased realism in the detector description
 - Realistic geometry of most subsystems: Individual modules in trackers, engineering details (mechanical supports, electronics, cooling, cabling, ...)
 - Inclusion of dead material, cracks, ...
 - ▶ Material budget estimates based on R&D activities
 - Improved reconstruction software
 - New generation of PandoraPFA
 - Proper treatment of silicon strips
 - Completely new Kalman-Filter-based tracking
 - New flavor tagging based on boosted decision trees trained with fully simulated events

ILD Material & Performance



- Realistic description of material budget

Tracking or flavor tagging performance



- PandoraPFA performance exceeding requirements over wide energy range

ILD Physics Performance

Do we dare to show something here? If yes, which analysis?

Something on gg->had background mitigation with k_t jet finding?

Summary