

LCWS14/20141008

STF Cryomodule Status



LINEAR COLLIDER COLLABORATION
Designing the world's next great particle accelerator

NAKAI Hirotaka

KEK


in collaboration with



LINEAR COLLIDER COLLABORATION
Designing the world's next great particle accelerator


HARA Kazufumi, HAYANO Hitoshi, HONMA Teruya,
HOSOYAMA Kenji, KAKO Eiji, KIMURA Nobuhiro, KOJIMA Yuuji,
KONDO Yoshinari, NAKANISHI Kota, YAMAGUCHI Seiya
and YAMAMOTO Akira (KEK)

1. Concepts of STF cryomodules (STF CM-1 + CM-2a)
2. Status of STF cryomodules
3. Current schedule



Cooling Scheme of Cryo-string

Cited from ILC-TDR

- Design of STF CM-1 based on ILC-TDR
- Two types of cavities in STF CM-1
 - Deference in tuner position
 - 4 cavities of each type (8 cavities in total)
- One superconducting quadrupole (sc quad) magnet in STF CM-1
- Cryomodules connected with flanges for making various configurations possible
 - Head unit : connection to cryogenic system
 - STF CM-1 (8 cavities + 1 sc quad magnet fabricated at FNAL)
 - STF CM-2a (4 cavities)
 - End unit : liquid helium level detection




End Unit for Liquid Level Detection




Downstream Side View

End Unit of STF Cryomodule



Liquid Helium
Level Sensor
Feed Through


- Design of STF CM-2a modified to check CW operation feasibility
 - Larger 2K 2-phase supply line ($\phi 76.3 \rightarrow \phi 89.1$)
 - Electric heaters attached to simulate dynamic heat load from superconducting cavities
- Usage of liquid nitrogen for 80K thermal shield instead of 40K thermal shield cooled by helium gas
- Conduction cooling of sc quad magnet
 - Aluminum strips from 2K 2-phase pipe



2K 2-phase pipe
2K helium gas return pipe
5K supply line
8K return line
(5K thermal radiation shield)
40K supply line --> 80K supply
80K return line
(40K thermal radiation shield)

Cited from ILC-TDR

Superconducting Quadrupole Magnet



- **Estimated heat load at 2K**

- Capture cryomodule : 8 W (static) + 2 W (dynamic) = 10 W
- CM-1 : 17 W (static) + 8 W (dynamic) = 25 W
- CM-2a : 11 W (static) + 4 W (dynamic) = 15 W
- SC quad magnet : 4 W (static)
- 2K refrigerators : 2 W x 2 = 4 W
- Total : 44 W (static)

- **2K refrigeration power**

- 7 W/pump unit x 4 units = 28 W at 2 K so far
- 10 W/pump unit x 2 units = 20 W at 2 K added this time
- Total : ~50 W at 2 K

STF Enhanced Helium Gas Pumping System













STF Cryogenic System Configuration






- Two wire position monitors to measure vertical displacement of cavities and gas return pipe (CM-1)
- Eight optical windows for Laser displacement sensors to measure vertical displacement of gas return pipe (CM-1)
- One beam position monitor (CM-1)
- Two potentiometers to measure axial displacement of gas return pipe (CM-1)
- One superconducting liquid helium level sensor in end unit




Vacuum vessel of STF CM-1 consists of 3 parts


- Established technique and machine tools
- Manufactured in limited period
- Limitation of delivery opening of the tunnel

Wire Position
Monitor Ports





STF CM-1 Current Leads of SC Quad Magnet



- Assembly of STF CM-1 complete in January, 2014
- Assembly of STF CM-2a complete in May, 2014
- Connection to cryogenic system complete in June, 2014
- Completion inspection by the prefectural government in July, 2014 → Passed already
- First cool down of STF CM-1 and CM-2a in October, 2014 (capture cryomodule excluded)
- First excitation of sc quad magnet with Fermilab colleagues in November, 2014