



LINEAR COLLIDER COLLABORATION

Designing the world's next great particle accelerator

The ILC positron source options


Status of e^+ sources discussion (our view)

- Source options
 - undulator based source (baseline, TDR)
 - **Polarized e^+ beam**
 - Electron driven
 - **Unpolarized e^+ beam**
- It seems there are strong intentions to establish the e^- driven source as baseline, at least for the 250GeV option. Main claims:
 - e^+ target technology has not been confirmed *no showstopper in view!*
 - e^+ polarization as update *why? no reason.*
 - e^- driven scheme is 'safe' *why? never proven.*
- Recently (also at LCWS17) a cost estimate comparison was presented by K.Yokoya
- Main problem, in particular for the undulator based source: resources

Undulator based e⁺ source

TDR 2012

- Source scheme;
 - parameters updated for $E_{cm} = 250\text{GeV}$:
undulator length
Ushakov



- Target:
 - wheel $\varnothing 1\text{m}$
 - photon beam ($\sim 60\text{kW}$) \Leftrightarrow energy deposition in target $\geq 2\text{kW}$
 - Target thickness 1.48cm Ti6Al4V for $E_{cm} \geq 350\text{GeV}$
 - Target thickness 0.7cm Ti6Al4V for $E_{cm} = 250\text{GeV}$**
 - Spinning in vacuum with 2000rpm (100m/s)
 - Cooling by thermal radiation**
- Issues:
 - e⁺ source at the end of ML \rightarrow all parameters **have to be optimized for each E_{cm}**
 - Source design and test of prototypes

Urgent tasks for the undulator source

- Calculation and design of target cooling system
 - Simulation of temperature and stress distribution in target wheel is most urgent and necessary before engineering design
 - *We do not see any showstopper for cooling by thermal radiation*
 - With 125GeV e- beam higher peak load on matching device. This is problem for the flux concentrator. Masks? QWT instead of FC should work (simulations only so far)
- Target wheel engineering design
 - After simulations, **prototyping is required** *money and manpower required!*
 - Check and optimize cooling efficiency using stationary target piece
 - Full wheel test including bearings
- Other issues
 - Design of OMD
 - Flux concentrator design work and prototyping (LLNL) stopped in 2012)
 - Photon dump (high power photon beam with small beam size; cannot be swept)
 - Shielding of target region
 - Target replacement scenario

Cost of Undulator System (K. Yokoya, LCWS17)

- TDR quotes 228 MILCU (accelerator components) and 72 MILCU for the CFS for the undulator e⁺ source.
- However, several design changes since TDR
 - **Undulator scheme:**
 - The undulator section must be lengthened 147m→231m for positron production at E_e=125GeV
 - TDR adopted 10Hz operation with 147m undulator
 - The beam dump of spent electron after photon production is needed for 10Hz operation. This will not be built in the first stage.
 - Auxiliary positron source will not be constructed, perhaps (majority of CRWG. It is not useful enough)
 - 72 MILCU for CFS could not be → number will not be used.
 - The extension for the undulator length 147m → 231m is already included in the tunnel (length for the TDR undulator scheme is 1678m)
 - ML tunnel cost for the 3GeV compensation
 - CFS cost for the dogleg is already included in positron source in TDR

Basic Cost of Undulator Scheme

(for comparison with e-driven)

K. Yokoya, LCWS17

- values were converted from MILCU to OkuYen

We use the same policy which we used when we converted TDR cost in MILCU to JYen for MEXT

1 MILCU = 1.09 OkuYen for tunnel civil engineering


1 MILCU = 1 OkuYen for CFS others and components

| | Accelerator | CFS |
|---------------------------|--------------|-------------|
| TDR | 227.5 | 67 |
| Longer undulator | 13.0 | 0 |
| 3GeV compensation | 27 | 7.3 |
| Dogleg | 21 | (1) |
| Beam dump for 10Hz | - 7.7 | 0 |
| Auxiliary positron source | -5.9 | 0 |
| SUM | 273.9 | 74.3 |

(1) CFS cost for dogleg is already included in TDR

Basic Assumptions for e-Driven Scheme

- Number of bunches per pulse 1312
- Number of positrons per bunch 3×10^{10} (incl. margin)
- Beam pulse structure
 - Repetition 5Hz : 200ms interval
 - 20 times $0.48 \mu\text{s}$ pulse in 63ms (300Hz)
 - Bunch distance 6.15ns
 - No pulse in the rest 137ms



Sum of Accelerator System e- driven

K. Yokoya, LCWS17

| | |
|---|--------|
| Electron drive linac (incl. electron gun) | 58.38 |
| Target system (excl. linac) | 16.50 |
| L-band capture linac | 32.80 |
| L+S band booster linac (incl. chicane) | 158.84 |
| Energy compressor | 5.68 |
| others | |
| Sum | 272.2 |

- ‘Others’ should include (but level of a few OkuYen)
 - photon&electron dump after capture linac
 - positron tuning dump
 - Electron dump right after drive linac (perhaps needed)
 - Beamline from end of energy compressor to DR

Comparison of the Basic Cost

K. Yokoya, LCWS17

| | Undulator | e-Driven |
|-------------|------------|------------|
| Accelerator | 274 OkuYen | 272 OkuYen |
| CFS | 74 OkuYen | 44 OkuYen |
| Sum | 348 OkuYen | 316 OkuYen |

Not included here:

**cost saving due to higher effective luminosity for
Undulator source !**

Final Cost Comparison

K. Yokoya, LCWS17

| | Undulator | e-Driven |
|--|-----------|----------|
| Basic cost (1) | 348 | 316 (2) |
| Empty space for timing (3) for 31.5 MV/m | 26 | |
| for 35 MV/m | 46 | |
| Sum for 31.5 MV/m | 374 | 316 |
| 35 MV/m | 394 | 316 |

(1) components+CFS, including 3GeV compensation, dogleg

(2) Assume the space for undulator+photon drift is eliminated.

If reserved, the cost increases by ~23 OkuYen

(3) CFS + RTML beam line + main beam line. Only the positron wing

- Luminosity upgrade is source technology dependent, it is not covered here.....*lots of open questions concerning shielding to e-driven source from our side!!!*
- Lumi upgrade propably easier with undulator source
- More details see in Yokoya's talk at LCWS'17, <https://agenda.linearcollider.org/event/7645/contributions/40017/attachments/32323/49050/PositronSourceComparison-LCWS2017.pdf>

e+ polarization:

expect $\sim 30\%$ for $E_{cm} = 250\text{GeV} \rightarrow$ effective luminosity for s-channel processes is enhanced by 24% ($P_e=80\%$)

à **Shorter running time**

à **Cost reduction**

So far, this fact has never been included into cost estimates!

e⁺ source ‘undulator group’

- Currently only DESY/Uni HH
 - SR, Andriy Ushakov (contract until ...18), Felix Dietrich (engineer, contract until 7/18); Khaled Alharbi (PhD student from Saudi Arabia) and myself
- Topics:
 - Undulator based source:
 - Parameter optimization
 - Target temperature and cooling
 - Target wheel design
 - Design preparation for prototyping
 - Studies take into account a realistic undulator B field based on measurements of prototype modules manufactured in UK
 - Photon dump design (together with P. Sievers, CERN, some recent activity also started in Japan)
 - Shielding & radiation aspects at the e⁺ source
 - Experimental tests to study and confirm material resistance against high cyclic and long-term load
 - To minor extent also contribution to studies for the e⁻ driven scheme

Further activities and plans at DESY&UHH

- E-beam at Mainz: we had already successful runs at 3.5 MeV and 14 MeV
 - 3/16, 11/16, 1/17, 3/17,.... next run probably begin 2018
 - generating similar load as for ILC target within short time
 - several targets, different thickness,
 - targets survived, but changes in structure: IPAC proceeding, <http://inspirehep.net/record/1626363/files/tupab002.pdf>
 - we also have a set-up to measure the emissivity
 - still targets under analyses: detailed laser scanning etc.
- stay tuned, interesting results need to be confirmed

New Plans for MAMI

- Current grant proposal foresees runs with electrons up to 180 MeV
 - get required PeakEnergyDepositionDensity within short time
 - expect higher rise in ΔT ($\sim 100^0$ - 200^0)
 - short-term overloading
- Precise analysis afterwards:
 - T-rise, thermic stress
 - structure, hardness, deformation
 - modelling of deformation, cracks etc.
- Methods:
 - Laser scanning etc. (started already)
 - synchrotron scattering (new!)

New Plans for DESY

'ex-situ'

- Using PETRA-3 beam for analyzing material
 - high-energetic synchrotron radiation of high brilliance: röntgen diffraction
 - γ -beam practically no divergence
 - **point-like analysis of material** (beam $<200\mu\text{m}$)
 - understanding of micro structure
 - high-energetic radiation (50keV-200keV) allows to analyse material of several mm thickness!
 - exactly what we need,.....
- Planned: e.g. study different Ti-alloys, which phase, etc.

Further new Plans for DESY

'in-situ'

- New installation of e-beam at 1-10 MeV
 - mean current strength of $\sim 600\mu\text{A}$ (100 Hz)
 - material tests not only with Ti-alloy, also WF
 - design study for shielding
- **Further idea:** use e-beam directly at PETRA-3
 - allows 'in-situ' target tests
 - *observe changes in target structures 'online'!*

Conclusions

- No showstopper for the baseline source, but engineering work needed....more manpower, please!
- e- driven source not yet in such mature level: shielding, vacuum requirements, engineering design still under study....
- cost estimates show equal footing for both design
- should be very carefully interpreted.....made assumptions are not **always** on 'equal footing'!
- Further options: lumi upgrade, polarization upgrade.....but we do need it for the physics case
- Exciting material results ongoing at Mainz, but with improved material analysis via laser scanning + diffraction technique
- Promising new test on the target materials planned here at DESY facilities even 'in-situ' via diffraction technique!
- ***Stay tuned! ...Lots of interesting results are going to happen!***





Questions (1)


K. Yokoya, LCWS17

- The following items might be accounted for the cost comparison.
- The 250GeV stage that we are studying now (option C, Option D) includes some empty tunnel for global timing adjustment for undulator scheme, which is not necessary for e-driven case. Should we eliminate it from the beginning?
 - Rigorously speaking, the timing constraint is necessary in the positron wing only. The empty tunnel in the electron side is added for future extension to higher CM energy
 - The empty space is larger if we assume 35MV/m rather than 31.5MV/m. Can we cut this space? (less margin for 250GeV)
 - In the present staging study we assume we do not change the DRs because of the presently available manpower. It is certainly possible to choose a DR circumference which makes extra empty tunnel unnecessary for timing adjustment

Questions (2)

K. Yokoya, LCWS17


- Should the space of the undulator (and subsequent photon drift) be reserved for later upgrade?
 - The tunnel of this region is laser-straight in TDR. Presumably, we can manage from beam dynamics view point, even if it is bent. (BDS part must still be laser-straight)
 - Note: to reserve this space does not immediately mean that we can go to undulator scheme any time
- Should the dogleg of electron beam line after undulator be eliminated (different tunnel layout)? This brings about further cost reduction but a pair of doglegs (not a single dogleg) would be needed for later upgrade to undulator source if it is not implemented.



250GeV Stage for Undulator Scheme

K. Yokoya, LCWS17

- Option C




↑
Not for timing.
Not included in
the
comparison


Tunnel for e-Driven Scheme

K. Yokoya, LCWS17

- With undulator/dogleg space



- Without undulator/dogleg space



Final Cost Comparison

K. Yokoya, LCWS17

| | Undulator | e-Driven |
|--|-----------|----------|
| Basic cost (1) | 348 | 316 (2) |
| Empty space for timing (3) for 31.5 MV/m | 26 | |
| for 35 MV/m | 46 | |
| Sum for 31.5 MV/m | 374 | 316 |
| 35 MV/m | 394 | 316 |

- (1) components+CFS, including 3GeV compensation, dogleg
- (2) Assume the space for undulator+photon drift is eliminated. If reserved, the cost increases by ~23 OkuYen
- (3) CFS + RTML beam line + main beam line. Only the positron wing

Luminosity Upgrade (1)

K. Yokoya, LCWS17

- Here, we cannot avoid mentioning the technology
- Basic change for upgrade 1312→2625 bunches
 - Reinforce main linac RF system (common to und.&edriven)
 - Electron damping ring (common to und.&edriven)
 - More RF system
 - Faster injection/extraction kicker
 - Positron damping ring
 - Same as electron DR if the e-cloud instability allows doubled beam current.
 - The first stage has factor ~3 margin to the instability. So, high possibility to double the bunches
 - We will get sufficient info from superKEKB and 1st stage ILC
 - If not, add one more positron DR. The room reserved.

Luminosity Upgrade (2)

K. Yokoya, LCWS17

- Required change for e-driven source
 - Add one more positron DR (independent on electron-cloud)
 - Beam-loading compensation difficult with 3ns bunch spacing
 - ~166 MILCU
 - Might be possible with one e+ DR if not doubling the bunches
 - Increase the energy of drive electron 3 \rightarrow 4.8GeV
 - ~ 31 OkuYen (simple scaling)
 - Tunnel length extension unnecessary (determined by BDS length)
 - Re-inforce modulators of drive linac and booster
 - due to longer beam pulse
 - Assume tunnel width is large enough
- Required change for undulator source
 - Target technology not confirmed yet
 - Target wheel would be heavier
 - To add positron DR or not depends only on the electron-cloud issue
 - Re-inforce RF of booster linac