Energy Sum & nHits layerwise

Using DWC and AHCAL

Olin Pinto DESY, 17th December 2018








Energy Sum Layer wise

80 GeV

Energy sum per layer

Red: Data

Blue: Simulation 2533 pixels




nHits layer-wise

DESY.

Hits per layer

Red: Data


Blue: Simulation 2533 pixels



Nhits and Cog_Z


Data for 80GeV electron

hitsvscog



Centre of gravity

Run number: 61156




DESY. Page 5

Centre of Gravity

Offset applied to DWC


From Wire Chamber segxnsegy




DESY. Page 6


Hit Energy: Layer-wise Comparative study


Layer 2 and 3






Layer 4 and 5







Layer 6 and 7




Layer 8 and 9





Layer 10 and 11






Layer 12 and 13





Layer 14 and 15




Thank you

Basic event selection for 80 GeV electron – June 2018 data

Run number: 61156

- Number of hits: Between 200 to 300 hits
- Center of gravity along Z: 180 mm to 280 mm




Basic event selection for 80 GeV electron – June 2018 data

Run number: 61156

Centre of gravity X: Between 70 mm to 80 mm

Centre of gravity Y: Between -50 mm to -40 mm


Choosing 1cm in centre of a tile: Pick events with maximum amplitude



Saturation Correction

80 GeV electron June data, Run number: 61156


Saturation Correction for 80 GeV electron - June data




Saturation Correction

80 GeV electron June data, Run number: 61156

The transition region of HG-LG around 5 MIP not fully understood






BACKUP


Gain Calibration

May 2018

- Fitted channels from each LED voltages are combined.
- May: Short LED no power pulsing run.
 - Gain distribution for May which consists only AHCAL(21, 888 channels). 94% channels fitted
 - Remaining 1373 channels acquire gain value from the mean of the corresponding chip.




RMS of the gains from chips



Gain Calibration

June 2018

- Gain distribution from June, includes the Tokyo layer (22464 channels).
- Long LED no power pulsing run on 25.06.2018



RMS

624

0.245

0.06502


Gain Calibration

October 2018

AHCAL + Tokyo layer.

DESY. | Gain calibration, SiPM saturation | O.Pinto, 12.10.2018

- Long LED power pulsing run on 17.10.2018
- 20 mV steps with 2000 cycles each run.




98% channels fitted

Page 23

Hit K


Data and MC

HitK Data and MC




Hit energy


At lower MIP values



Saturation Correction

100 GeV electron June data, Run number: 61217







Saturation Correction

100 GeV electron June data, Run number: 61217










Gain Correlation

Between two days






Gain of Tail Catcher

Module 43 to 54


Total Gain Distribution



Light Yield

Pre-shower

light yield of module_42




DESY. | Presentation Title | Name Surna , Page 30

Light Yield

Tail Catcher

New one here light yield of Tail catcher




DESY. | Presentation Title | Name S

Light Yield


Tokyo layer

light yield of module_41




Hit energy for 80 GeV and 100 GeV electron

Layer 2




Hit energy layer wise

80 GeV electron



Hit energy layer wise

100 GeV electron



Conclusion

	Gain	
AHCAL	Pre-Shower	Tail Catcher
~16 ADC	Varying from ~15-16 ADC	~15 and ~30 ADC
	Light Yield	
AHCAL	Pre-Shower	Tail Catcher
~14 pix/MIP	Varying from ~14 pix/MIP	~13 and ~27 pix/MIP
	Saturation Correction	
2433	2533 and 2668	2533
Under-estimates the data	Over-estimates the data	Agrees to certain extent with data