



# Experimental studies of Nb material at KEK (FY2018 – FY2021 and to FY2022)

IDT WG2 SRF-Group meeting

**18 Jan. 2021**

T. Saeki (KEK)

# Objective of our studies at KEK









- The studies are aiming at **the cost-effective Nb materials** for the mass-production of ILC SRF-cavities.
- The Nb materials should promise the **good performance of SRF-cavities** and enough **mechanical properties to pass HPGS\*** regulation of Japan.  
\*HPGS: High Pressure Gas Safety
- Focusing on:
  - \* **Purity/RRR** (including **Ta-contents**)
  - \* **Grain-size** and **fabrication methods** (forging, rolling, and direct-slicing etc.)
  - \* Combinations to various surface treatments (standard and advanced recipes)

## Definition of words in this presentation







- **FG** = (Fine Grain), **MG** = (Medium Grain), **LG** = (Large Grain)  
Grain size: < 0.1 mm, < 1 mm, >> 1 cm
- **High-RRR** = (RRR  $\geq$  300)
- **Mid-RRR** = (300 > RRR > 200)
- **High-Ta** = (Ta > 1000 ppm)
- **Low-Ta** = (Ta < 100 ppm)
- **HPGS** = High Pressure Gas Safety regulation

# Overview of studies

Nb materials	Cavities	FY2018	FY2019	FY2020	FY2021	FY2022
LG Mid-RRR High-Ta		Two 9-cell cavities were fabricated	VT Eacc < 35MV/m	VT Eacc < 35MV/m		
LG High-RRR Low-Ta				Two 3-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	
LG High-RRR High-Ta	 			Two 3-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	
MG High RRR Low-Ta	 			Two 1-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	VT
						One 9-cell cavity will be fabricated

# RRR and Ta-fraction studies

# Overview of studies

Nb materials	Cavities	FY2018	FY2019	FY2020	FY2021	FY2022
LG Mid-RRR High-Ta		Two 9-cell cavities were fabricated	VT Eacc < 35MV/m	VT Eacc < 35MV/m		
LG High-RRR Low-Ta				Two 3-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	
LG High-RRR High-Ta	 			Two 3-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	VT
MG High RRR Low-Ta	 			Two 1-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	One 9-cell cavity will be fabricated


# Mid-RRR (LG-Nb, High-Ta)

300 > RRR > 200

Studies from FY2018 to FY2020



Mid-RRR (LG-Nb, High-Ta) 9-cell cavities have not reached 35 MV/m.



KEK-4, KEK-5



5

Nb Venders: C, Mid-RRR (LG-Nb, High-Ta)



Two of them have not achieved ILC spec. Eacc = 34 MV/m







Slide by Dohmae  
2020-Dec  
IHEP meeting



9

We have concluded that High RRR is necessary for high SRF performance.

# Overview of studies

Nb materials	Cavities	FY2018	FY2019	FY2020	FY2021	FY2022
LG Mid-RRR High-Ta		Two 9-cell cavities were fabricated	VT Eacc < 35MV/m	VT Eacc < 35MV/m		
LG High-RRR Low-Ta				Two 3-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	
LG High-RRR High-Ta	 			Two 3-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	
MG High RRR Low-Ta	 			Two 1-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	One 9-cell cavity will be fabricated



# High-RRR (LG-Nb, Low-Ta)

RRR > 300



Studies from FY2020 to FY2021 (now)





High-RRR (LG-Nb, Low-Ta) 3-cell cavities have reached > 35 MV/m.

Two 3-cell cavities were fabricated in Mar. 2021.



R16, R16b







Nb Venders: A + C, High-RRR (LG-Nb, Low-Ta)



R-16: VT1 (25 Nov. 2021),  $E_{acc} = 37 \text{ MV/m}$  (Initial  $E_{acc} = 41 \text{ MV/m}$ ).  
 R-16b VT1 (16 Dec. 2021),  $E_{acc} = 39 \text{ MV/m}$  (Initial  $E_{acc} = 40 \text{ MV/m}$ ).

We have decided to focus on Nb material with RRR > 300.

# Overview of studies

Nb materials	Cavities	FY2018	FY2019	FY2020	FY2021	FY2022
LG Mid-RRR High-Ta		Two 9-cell cavities were fabricated	VT Eacc < 35MV/m	VT Eacc < 35MV/m		
LG High-RRR Low-Ta				Two 3-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	
LG High-RRR High-Ta				Two 3-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	
					Two 9-cell cavities are under fabrication	VT
MG High RRR Low-Ta				Two 1-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	
						One 9-cell cavity will be fabricated


# High-RRR (LG-Nb, High-Ta)

RRR > 300

Studies from FY2020 to FY2021 (now)



High-RRR (LG-Nb, High-Ta) 3-cell cavities have reached > 35 MV/m.

Two 3-cell cavities were fabricated in Mar. 2021.



R17, R17b

Nb Venders: B + C, High-RRR (LG-Nb, High-Ta)









R-17: VT2 (09 Spt. 2021)  $E_{acc} = 35 \text{ MV/m}$


R-17b: VT3 (28 Spt. 2021)  $E_{acc} = 37 \text{ MV/m}$  (Initial  $E_{acc} = 42 \text{ MV/m}$ )

Ta-fraction is not sensitive to SRF performance if RRR > 300.

# Overview of studies

Nb materials	Cavities	FY2018	FY2019	FY2020	FY2021	FY2022
LG Mid-RRR High-Ta		Two 9-cell cavities were fabricated	VT Eacc < 35MV/m	VT Eacc < 35MV/m		
LG High-RRR Low-Ta				Two 3-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	
LG High-RRR High-Ta	 			Two 3-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	
					Two 9-cell cavities are under fabrication	VT
MG High RRR Low-Ta	 			Two 1-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	
						One 9-cell cavity will be fabricated

# Low-Ta vs. High-Ta (LG, High-RRR)



Comparison of Low-Ta vs High-Ta



Ta-fraction is not sensitive to the SRF performance if RRR > 300.


Difference of Q values are within the measurement error.

## Grain-size studies

# Process flow of the industrial Nb production




FG Nb




Slide by Tokyo Denkai

# Process flow of the industrial Nb production

LG Nb



Picture of half cup




LG-Nb realized very good cost performance.  
But LG-Nb material causes broad mechanical strength distribution (less uniformity).  
(Minimum strength becomes low compared with that of FG-Nb material.)



# Process flow of the industrial Nb production



MG Nb



Slide by Tokyo Denkai

Uniformity of Nb material is achieved by Medium-Grain (MG) structure.


# Manufacture methods of Large-Grain / Medium-Grain Nb discs



Center for Applied Superconducting




Nb melting




Niobium ingot (Raw material)


Direct slice of LG ingot



Ingot, as it is



Slicing image by wire-saw



LG Nb



**Large Grain (LG) Disc**  
Grain Size  $\gg 1$  cm

- Aiming for clean, mechanically stable, and cost-effective SRF cavity production.


Direct slice of MG ingot



Ingot, forged and annealed



Slicing image by wire-saw



MG Nb

**A New Approach: Medium Grain (MG) Disc**  
Grain Size  $< 1$  mm

\* The “Nb forged ingot” technology originated by **ATI**, and SRF (GHz) cavities planned to be fabricated and RF tested by **KEK** and **JLab**, to qualify this approach, in collaboration of **ATI**, **ODU/BSCE**, **JLab**, and **KEK**.

# MG-Nb demonstration by 1.3 GHz SRF Cavity at KEK

“Nb RRR” Billet, annealed



Sample location from forged ingot




Parameters	Nb sheet (FG) (Spec. Eu-XFEL as Reference)	Nb forged ingot (MG) Measured
RRR	$R_{RT}/R_{4.2K} \geq 300$	$R_{RT}/R_{TC}$ 450 523
Re-crystallization	100 %	100 %
Grain size (ASTM) Edge, Mid., Center	4 ~ 6	2, 1, 1.5
Grain size (mm) Edge, Mid., Center	< 0.05	0.2, 0.25, 0.21
Y.S.-0.2% (RT)	$\geq 50$ MPa	61 MPa
T.S. (RT)	$\geq 140$ MPa	141 MPa

MG-Nb: Good mechanical uniformity

0.02 inch ( 50  $\mu$ m)









ATI



Grain Size: 0.2 ~ 0.3 mm  
Mechanical stability  
may be expected

# Overview of studies




Nb materials	Cavities	FY2018	FY2019	FY2020	FY2021	FY2022
LG Mid-RRR High-Ta		Two 9-cell cavities were fabricated	VT Eacc < 35MV/m	VT Eacc < 35MV/m		
LG High-RRR Low-Ta				Two 3-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	
LG High-RRR High-Ta				Two 3-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	
					Two 9-cell cavities are under fabrication	VT
MG High RRR Low-Ta				Two 1-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	
						One 9-cell cavity will be fabricated

# MG-Nb material (High-RRR, Low-Ta)

Results of MG single-cell cavities.  
R18, R18b (vs. R9 / FG single-cell cavity).

## R18 vs R18b vs R9



- R18, R18b were fabricated using MG discs
  - Inner surface of R18 was mechanically polished during fabrication (R18b was not)
- VT of R18: 38.8 MV/m with  $Q_0=1.5 \times 10^{10}$
  - VT of R18b: 35.4MV/m with  $Q_0=1.76 \times 10^{10}$

**Two MG-Nb single-cell cavities have reached > 35 MV/m**

# Mechanical properties of Nb material

Objective: To pass HPGS regulation

# MG Nb material / Tensile tests etc.



Mechanical strength of **MG-Nb** samples were tested and **the results were presented in SRF2021.**

SRF2021  
MOPCAV004  
A. Kumar  
(July 2021)

The MG-Nb samples were BCP'ed (chemical polished) before tests. There was some **brittleness and low elongation** of **MG-Nb** samples in the low temperature tensile-tests (**hydrogen absorption problem?**).


## MECHANICAL PROPERTIES OF DIRECTLY SLICED MEDIUM GRAIN NIOBIUM FOR 1.3 GHZ SRF CAVITY

A. Kumar, T. Saeki, T. Dohmae, S. Michizono, M. Yamanaka, Y. Watanabe, K. Abe, A. Yamamoto, High Energy Accelerator Research Organization (KEK), Tsukuba, Japan  
N. Lannoy, A. Fajardo, ATI Specialty Alloys and Components, Albany, Oregon, USA  
G.R. Myneni, Jefferson Laboratory, Newport News, Virginia, USA / BSCE Systems, Yorktown, Virginia, USA





### Introduction

- ILC-250 is an electron-positron collider that requires 7800 1.3 GHz SRF cavities.
- The TDR is already published but the cost of its construction is a major hurdle.
- High purity Niobium (**costly**) is used to manufacture 9-Cell 1.3 GHz SRF cavity.




### Results and Discussion

- ATI MG Nb billet was sliced into 65 disks and specimens from top two and bottom two disks were cut for tensile testing.
- All disks were chemically polished, specimens were wire EDM cut and then chemically polished again (see fig below).
- A set specimens were annealed at 800 °C for 3 hrs and the remaining ones were not, considered as in As-received condition (ASR).
- Tensile tests were performed in room temperature and in liquid helium.



# Mechanical strength comparison of FG/MG/LG at RT

Results in average of all data ( Dec. 2021)




- MG Nb closer to FG Nb than LG Nb at room temperature.
- Elongation is not considered for high pressure code.
- High elongation necessary for press forming of Nb half cells.

**Mechanical strength of MG-Nb achieved the criteria of HPGS regulation.**



# Mechanical strength comparison of FG/MG/LG at LHe-T









**Strength of MG-Nb at LHe-T is better than LG-Nb.**

**Brittleness and low-elongation of MG-Nb are not observed at LHe-T after annealing process.**



# Plan in FY2022


# Overview of studies

Nb materials	Cavities	FY2018	FY2019	FY2020	FY2021	FY2022
LG Mid-RRR High-Ta		Two 9-cell cavities were fabricated	VT Eacc < 35MV/m	VT Eacc < 35MV/m		
LG High-RRR Low-Ta				Two 3-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	
LG High-RRR High-Ta				Two 3-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	
					Two 9-cell cavities are under fabrication	VT
MG High RRR Low-Ta				Two 1-cell cavities were fabricated	VT Eacc > 35MV/m ILC spec. achieved	
						One 9-cell cavity will be fabricated

# Plan-1: Demonstration of Nb material of High-RRR and High-Ta.



LG  
High-RRR  
High-Ta



Two high-RRR/high-Ta 9-cell cavities will be fabricated and Vertically-Tested (VT) in FY2022.

Nb material of high-RRR/high-Ta is cost-effective, and has good SRF performance.

## Plan-2: Demonstration of MG-Nb 9-cell cavity SRF performance




MG  
High-RRR  
Low-Ta



One MG 9-cell cavities will be fabricated and Vertically-Tested (VT) in FY2022.

MG-Nb material is cost-effective, and has both good SRF performance and stable mechanical properties to pass HPGS regulation.



# Plan-3: Reproducibility verification of mechanical properties of MG-Nb billet/disk



MG-Nb billet#	Delivery to KEK	Billet dimension	Studies
<u>Billet #1</u>	Feb. 2021	D 260 mm L 200 mm	Mechanical properties were already tested. (Tensile tests at RT and LHe-T)
First Trial of MG-Nb Forging + HT			One TESLA-shape 9-cell cavity will be fabricated.
<u>Billet #2</u>	Mar. 2022	D 260 mm L 270 mm	Mechanical properties will be tested. (Tensile tests at RT and LHe-T + charpy impact tests)
Objective: <b>Reproducibility</b>			Two TESLA-shape 9-cell cavities will be fabricated (not scheduled yet).
<u>Billet #3</u>	Dec. 2022	D 260 mm L 270 mm	Trial to improve elongation in production process in vender.
Objective: <b>Improvement</b>			Mechanical properties will be tested. (Tensile tests at RT and LHe-T + charpy impact tests)
			Two TESLA-shape 9-cell cavities will be fabricated (not scheduled yet).

# Summary



- **Nb**: High RRR is necessary for high SRF performance.
- **Nb**: Ta-fraction is not sensitive to the SRF performance.
- **MG-Nb**: Cost effectiveness, good SRF performance & mechanical properties to pass HPGS regulation are demonstrated.
  - SRF Performance of **MG single-cell cavities** reached **the ILC spec.** as well as LG cavities.
  - MG elongation improvements is anticipated for ILC mass-production (yield rate of press-forming of half-cell).
- **LG-Nb**: Cost effectiveness & good SRF performance, but the mechanical strength stability is the issue to be improved to pass HPGS regulation.